

FIRST RE-ESTABLISHMENT

GCDB 300640

Quarter corner common to Sec. 5 and 4, Twp. 31 South, Range 2 East, W.M.

Fd., firmly set, the original 18x13x5 ins. (45x33x12 cm) stone, record; 15x12x5 ins. (38x30x12 cm) mkd. "1/4" on West face, as recorded by P.Applegate n 1891.

I replace said stone with a 1x36 ins. (2.5x91 cm) G.I. pipe, set 30 ins. (76.20 cm) in the ground with a 2 1/2 ins. (6.3 cm) bronze disc mkd.: JACKSON COUNTY 1978

T31S R2E
5 | 4
1/4S

The single remaining original bearing tree, a Hemlock (record, larch) now 28 ins. (71.12 cm) diam, with healed blazes brs. N89°W, 94.7 ft. (28.86 m) to center of tree. Record: N89°W, 92.40 ft. (28.16 m).

I deposit original stone alongside corner and mk. a new tree C.S. B.T.:

Hemlock, 28 ins. (71 cm) diam. brs S79°E, 61.80 ft. (18.83 m).

Corner lies on blazed N-S line about 250 ft. (76.20 m) South of location marker on an 18 ins. (45 cm) diam. hemlock alongside road C. S70°E.

June 7, 1978

B.Malotte

R.Frost

Approved by: Ed McGinty

Co. Surveyor

FILED

Date: 3-19-2012 By: JC

This survey consists of:

Map: _____

Narrative: _____

Corner Rpt: CS 65/76-33

**DOUGLAS COUNTY
SURVEYOR**

C.S. File No 65/76-33