

FIRST RE-ESTABLISHMENT

GCDB 640600

DOUGLAS COUNTY
SURVEYORQuarter corner common to Sec. 1 and 12, Twp. 30 South, Range 3 East, W.M. $V=18\frac{1}{2}^{\circ}$

Fd., projecting 2 ins. (5 cm.) the original 1 ins. (2.5 cm.) diam. iron pipe with G.L.O. brass cap mkd:

S1
 $\frac{1}{4}$ —
S12
1928

as recorded by H. Raymond in 1928.

Original bearing trees fd as follows:

White fir, 24 ins. (61 cm.) diam., with healed single blaze brs. $S16^{\circ}E$, 26.31 ft. (8.02 m.) to center. Record; $S26^{\circ}E$, 26.40 ft. (8.05 m.).Hemlock stump, 26 ins. (66 cm.) diam., 6 ft. (2 m.) high, marked " $\frac{1}{4}$ S1BT" in exposed single face, brs. $N72\frac{1}{2}^{\circ}W$, 35.25 ft. (10.74 m.) to center. Record: $N72\frac{1}{2}^{\circ}W$, 34.98 ft. (10.66 m.).

Note: mks on this tree appear to have been "knife scribed".

I mk a new tree CS BT:

White fir, 14 ins. (36 cm.) diam., brs. $N2^{\circ}E$, 53.17 ft. (16.21 m.) to center of tree at lower blaze.

Corner lies about 400 ft. (122 m.) west of location marker on 12 ins. (30 cm.) diam. fir stob, alongside road.

November 11, 1977

B. Malotte

R. Frost

Approved by: Ed McGinty

Co. Surveyor

SEE NEXT PAGE FOR 2ND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 640600

DOUGLAS COUNTY
SURVEYOR

Quarter corner common to Sections 1 and 12 of Township 30 South, Range 3 East, W.M.

Found at corner position exposed 2 ins. the 1 in. diam. galv. iron pipe with a 2½ ins. diam. brass cap set by the GLO in 1928 and marked:

S1
¼ ———
S12
1928

Aluminum post 1 ft. to the west of monument.

Bearing trees recorded by Herbert Raymond of the GLO in 1928 found and measured to center at base:

W. fir now 32 ins. diam. with healed single blaze brs. S 16° E, 26.8 ft. Record; 26.3 ft.

Hemlock high stump, rotted with "¼ S1 BT" in detached face brs. record; N 72½° W, 35.3 ft.

Bearing tree recorded on 1st Re-establishment in 1977 found with healed double blazes and measured to center at lower blaze:

W. fir now 25 ins. diam. brs. record N 2° E, 53.2 ft.

Marked new bearing trees "CS" "BT" and measured to center at lower blaze:

Hemlock 17 ins. diam. brs. S 84½° W, 48.1 ft.

P. pine 8 ins. diam. brs. N 4½° W, 12.1 ft.

Corner lies approx. 400 ft. west of gravel road.

May 31, 2007

B. Beeman

H. Durkee

Roger R. Roberts

Jackson County Surveyor

P. 128

V - 15° 40'