

OREGON CORNER RESTORATION FORM

Section 31 Township 24 South, Range 2 West
County Douglas Date 6 September 2012

Corner Description

N1/4 Corner
Section 31

FILED
Date: 9/18/2012 By: X
This survey consists of:
Map: _____
Narrative: _____
Corner Rpt: CS 65/77-34

DOUGLAS COUNTY
SURVEYOR

- Condition Report Only
- Not Found
- Renewed
- Unrecorded
- Surveyed In
- Referenced Out

Previous Renewals / Surveys, etc.

Monument (s) & Accessories Found: (Condition and Source)

- Found 1" dia. Iron post with BLM brass cap dated 1951
- 36" now 40" Fir, bears N.35°E., 69.0 ft., scribing visible on single face. Dist. to center of BT. (Found 32"dia.x 6' high stump with scribing visible)
- 40" now 42" Fir windfall, slid about 15' to north scribing visible on single face. Bearing & dist. to root hole N.26°W., 86.5 ft. (Not found)
- 26" Cedar snag, N.45°W., 66.4 ft., "W" nail & plate (Found 26"dia.x 5' high Cedar stump with nail and tag)

Monument Detail

Sketch

Monument Set (Procedures and Description)

None

New Accessories

- 13" D. Fir bears N18°E 5.8 ft., scribed 1/4 S30 BT
- 12" D. Fir bears S87°W 13.3 ft., scribed 1/4 S31 BT
- 16" D. Fir bears S65°E 39.9 ft., scribed 1/4 S31 BT

Location & Comments

Corner has steel post _____ Compass Declination 16° East
adjacent to it. _____ Firm/Agency Northwest Land
All BT's have orange painted _____ Surveying Inc.
bands and yellow tags. _____ Address P.O. Box 2827
 _____ Florence, OR 97439
 _____ Party Chief Ron Rice
 _____ Notes _____
 _____ Witness Jason Collver

Surveyor's Seal



RENEWS: 12-31-2012

C.S. FILE 65/77-34