

OREGON CORNER RESTORATION FORM

Section 31 Township 24 South, Range 2 West
County Douglas Date 6 September 2012

Corner Description

NE Corner
Section 31

Previous Renewals / Surveys, etc.

Monument (s) & Accessories Found: (Condition and Source)

- Found 2" dia. Iron post with BLM brass cap dated 1951
- 48" Fir sawed stump, S.74°E., 16.5 ft., fragmentary scribe on burned blaze. Rescribed "T24S R2W S32 CS BT" (Found with no marks)
- 16" Hemlock S.21°W. 105.2 ft. mkd: T24S R2W S31 CS BT (Found 32" Hemlock with healed face)
- Weyerhaeuser BT: 48" Fir stump S.77°W., 42.9 ft. (Found in same condition)

Monument Detail

Sketch

Monument Set (Procedures and Description)

None

New Accessories

- 20" D. Fir bears S32°E 6.9 ft., scribed T24S R2W S32 BT
- 19" D. Fir bears N72°E 28.1 ft., scribed T24S R2W S29 BT
- 23" D. Fir bears N6°E 33.6 ft., scribed T24S R2W S29 BT

Location & Comments

Corner has steel post _____ Compass Declination 16° East
 adjacent to it. _____ Firm/Agency Northwest Land
All BT's have orange painted _____ Surveying Inc.
bands and yellow tags. _____ Address P.O. Box 2827
 _____ Florence, OR 97439
 _____ Party Chief Ron Rice
 _____ Notes _____
 _____ Witness Jason Collver

Surveyor's Seal



RENEWS: 12-31-2012

C.S. FILE 65/77-36

FILED
 Date: 9-18-2012 By: JC
 This survey consists of:
 Map: _____
 Narrative: _____
 Corner Rpt: CS 65/77-36
 DOUGLAS COUNTY
 SURVEYOR

- Condition Report Only
- Not Found
- Renewed
- Unrecorded
- Surveyed In
- Referenced Out