

**RECORD OF SURVEY**  
**FOR: SENECA JONES TIMBER COMPANY**  
**NE1/4, SE1/4, SECTION 32, T.26 S., R.2 W., W.M.**  
**DOUGLAS COUNTY, OREGON**  
**7 MAY 2013**

FILED  
 DATE: 5-30-2013 BY: JC  
 THIS SURVEY CONSISTS OF:  
 MAP: CS 65/79-9  
 NARRATIVE: \_\_\_\_\_  
 CORNER RPT: \_\_\_\_\_

DOUGLAS COUNTY  
 SURVEYOR



**SECTION CORNER SECTIONS**  
 28,29,32,33  
 FOUND 2-1/2" ALUM. CAP UNDATED  
 WITH  
 THE FOLLOWING ACCESSORIES:  
 9" D. FIR BEARS N 30° W 43.0' -  
 HEALED FACE  
 11" D. FIR BEARS N 2° E 7.8' -  
 HEALED FACE  
 8" D. FIR BEARS S 40° E 13.3' -  
 HEALED FACE  
 27" R. CEDAR BEARS N 28° W 75.0' -  
 SCRIBING VISIBLE  
 OLDER ACCESSORIES  
 UNCHANGED FROM CS 65/70-3  
 STEEL POST ADJACENT TO  
 CORNER

**NARRATIVE:**

THE PURPOSE OF THIS SURVEY  
 WAS TO MARK TRUE LINE  
 BETWEEN SECTIONS 32 AND 33,  
 OF TOWNSHIP 26 SOUTH, RANGE  
 2 WEST OF THE WILLAMETTE  
 MERIDIAN AND TO ESTABLISH  
 THE MISSING QUARTER CORNER  
 AT PROPORTIONATE POSITION  
 BETWEEN SECTIONS 32 AND 33.

EXISTING NORTH AND SOUTH  
 SECTION CORNERS WERE TIED  
 BY TRAVERSE FOR THE MARKING  
 OF TRUE LINE AND THE SETTING  
 OF THE MISSING QUARTER  
 CORNER. NO EVIDENCE OF  
 ORIGINAL QUARTER CORNER  
 WAS RECOVERED.

TRUE LINE WAS MARKED WITH  
 RED PAINTED BLAZES, RED  
 FLAGGING, AND 5-1/2"  
 GALVANIZED STEEL POSTS, SET  
 AND AVERAGE INTERVAL OF 200'.

THE BASIS OF BEARING FOR THIS  
 SURVEY WAS THE 1911 GENERAL  
 LAND OFFICE RECORD FOR THE  
 ABOVE REFERENCED LINE.

THIS SURVEY WAS PERFORMED  
 USING A NIKON TOTAL STATION.

N 0°03'00" W 2630.03' [N 0°03' W 40 CHAINS]



**1/4 CORNER SECTIONS 32,33**  
 SET 2-1/2" ALUM. CAP, MARKED AS  
 SHOWN ON 5/8" X 30" REBAR AND  
 ESTABLISHED THE FOLLOWING  
 ACCESSORIES:  
 18" D. FIR BEARS S 21° E 10.5' -  
 BLAZED, SCRIBED 1/4 S33 BT  
 17" W. FIR BEARS N 22° E 24.7' -  
 BLAZED, SCRIBED 1/4 S33 BT  
 26" D. FIR BEARS N 38° W 32.6' -  
 BLAZED, SCRIBED 1/4 S32 BT  
 17" W. FIR BEARS S 73° W 14.7' -  
 BLAZED, SCRIBED 1/4 S32 BT  
 STEEL POST ADJACENT TO  
 CORNER

T26S R2W  
 1/4  
 S32 | S33  
 2013  
 54633LS

**SECTION CORNER SECTIONS**  
 4,5,32,33  
 FOUND 2-1/2" DCSO BRASS CAP  
 DATED 1967 WITH THE FOLLOWING  
 ACCESSORIES:  
 12" CEDAR BEARS S 21° W 21.4' -  
 SCRIBING VISIBLE  
 36" CEDAR BEARS N 36° W 37.1' -  
 HEALED FACE  
 54" D. FIR BEARS N 30° W - BARK  
 SCRIBE NO LONGER VISIBLE  
 24" CEDAR BEARS N 12° E 39.7' -  
 SCRIBING VISIBLE  
 7" ALDER BEARS S 7° E 27.5' -  
 SCRIBING VISIBLE  
 OLDER ACCESSORIES NOT  
 SEARCHED FOR, STEEL POST  
 ADJACENT TO CORNER

**LEGEND**



SET 1/4 CORNER  
 AS NOTED

SECTION CORNER  
 AS NOTED

[ ] 1911 GENERAL LAND  
 OFFICE RECORD DATA



Northwest Land Surveying, Inc.  
 P. O. Box 2827  
 FLORENCE, OR 97439 541-997-9201

REGISTERED  
 PROFESSIONAL  
 LAND SURVEYOR

*Ronald L. Rice*

OREGON  
 JULY 9, 2002  
 RONALD L. RICE  
 54633LS

EXPIRATION DATE: 12-31-2014

FILE NAME		
13-04.TRV		
SCALE	DATE	DRAWN BY
600 Ft/in	5-7-2013	RLR
JOB	REVISION	SHEET
GREENMAN 32	---	1/1

This map drawn with TRAVERSE PC Software