

FILED

Date: 10/30/2013 By: SC

This survey consists of:

Map: \_\_\_\_\_

Narrative: \_\_\_\_\_


Corner Rpt: CS 65/80-35 (2 pgs)

DOUGLAS COUNTY  
SURVEYOR

**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

**History of original corner establishment:** Angle Point 1134, Oregon Cascade Recreation Area

The Forest Service established this corner for the OCRA in 1990, which is 200 feet easterly and perpendicular to Forest Service trail no. 1457. They set an iron pipe, 2-3/8" outside diameter, 30" long, 28" in the ground with a 2 foot diameter mound of stone to the top, with a 2-1/2" diameter brass cap attached and marked as shown. They marked BTs: a 6" lodgepole pine, bears S. 86-1/2° E., 2.8 feet, scribed "OCRA I BT" on a single blaze; and a 4" western white pine, bears S. 84° W., 21.4 feet, scribed "X BT" on a single blaze.



**Description of corner evidence found:** September 26, 2013  
At the corner I found an iron pipe, 2-3/8" outside diameter, firmly set, flush with a 2 foot mound of stone, with a 2-1/2" diameter brass cap attached and marked as shown above.

From which the original bearing trees:  
- A 7" diameter lodgepole pine, bears S. 86-1/2° E., 2.8 feet, with partially healed double blaze.  
- A 4" diameter stump, bears S. 84° W., 21.4 feet, with a 4" diameter western white pine log alongside with scribe marks "X BT" visible on an unhealed single blaze.

**Description of monument and accessories I established to perpetuate the original location of this corner:** September 26, 2013  
And from which I add new references:  
- A 6-foot aluminum post driven 1.5 feet in the ground, bears S. 40-1/2° E., 1.8 feet, with Forest Service "Land Survey Monument" sign attached as a guard post.  
- A 5" diameter hemlock, bears S. 48° W., 36.7 feet, scribed "AP 1134 BT" on a single blaze.  
- An 11" diameter lodgepole pine, bears N. 54-3/4° W., 17.1 feet, scribed "OCRA AP 1134 BT" on a single blaze.

With a 20 second optical transit I sighted on the original SW BT with a bearing of S. 84° W. as my basis of bearings. Bearings are measured to the nearest 1/4°. Trees are measured to the center of the root crown. Tree diameters are at breast height. New bearing trees have a 3/4" brass washer, pre-marked "LS 2150", nailed to the BT portion of the blaze.

Witness: Robert Lee  
  
Leonard E. Herzstein, L.S. 2150  
Umpqua National Forest  
2900 NW Stewart Parkway  
Roseburg, OR 97471



AP 1134  
ORIG SE BT

