


RECORD OF SURVEY
 FOR: ROSEBURG RESOURCES CO.
 NW1/4, SEC. 32, T23S, R06W, W.M.
 DOUGLAS COUNTY, OR
 3/14/2014





REGISTERED
 PROFESSIONAL
 LAND SURVEYOR




OREGON
 ROBERT B. WARD JR.
 JULY 30, 1976
 LS 1091


EXPIRATION DATE: 6/30/14

LEGEND

-  FND 1/4 CORNER
-  FND SECTION CORNER
-  PROPERTY LINE BLAZED, PAINTED
FLAGGED & POSTED
-  [] BLM 1995 RECORD DATA



BASIS OF BEARING
 BLM 1995 DEPENDENT RESURVEY
 [S 88°56'30" W, 47.605 CH]
 S 88°56'30" W 3141.68'



SECTION CORNER 29/30/31/32
 FND: 3-1/4' BLM BRASS CAP DATED 1994
 WITH THE FOLLOWING ACCESSORIES;
 22" D-FIR BEARS N50-1/2°E, 71.3' - HEALED FACE
 17" D-FIR BEARS N12-1/2°W, 80.5' - HEALED FACE
 13" D-FIR BEARS S85-1/2°E, 15.2' - HEALED FACE
 19" D-FIR BEARS S71°W, 8.6' - HEALED FACE
 INVERTED BLM MONUMENT BEARS N11°W, 12.74' - FLUSH TO GRAOUND

1/4 CORNER 29/32
 FND: BLM BRASS CAP DATED 1994
 WITH THE FOLLOWING ACCESSORIES;
 14" D-FIR BEARS N4-1/4°E, 23.1' HEALED FACE
 13" D-FIR BEARS S61-1/2°E, 7.3' - HEALED FACE
 BROOKS CORNER BEARS N2°E, 69.9'
 NEW BT THIS SURVEY;
 21" MADRONE BEARS N33°W, 6.7' - SCRIBED "1/4 S29 BT"

 NORTHWEST Land Surveying, Inc.
 (541) 997-9201
 www.northwestlandsurveying.com

P.O. Box 2827
 Florence, OR 97439
 Fax (541) 902-0743

JOB 12-12

NARRATIVE

THE PURPOSE FOR FILING THIS SURVEY IS TO DOCUMENT A PROPERTY LINE SURVEY FOR ROSEBURG RESOURCES CO., THAT WAS PERFORMED IN MARCH OF 2012. ROSEBURG RESOURCES CO. HAS REQUESTED THAT ALL SURVEY WORK PERFORMED FOR THEM BETWEEN 2011 AND 2014 BE SHOWN IN A RECORD OF SURVEY. WHEN THE SURVEY WAS PERFORMED, NO CORNERS WERE SET, ONLY PROPERTY LINES WERE MARKED AS NOTED HEREON.

THIS SURVEY RESULTED IN MARKING THE TRUE LINE BETWEEN THE NW CORNER AND THE N 1/4 CORNER OF SECTION 32, T23S, R06W, W.M.

EXISTING CORNERS WERE TIED BY GROUND TRAVERSE FOR CONTROL AND HELD IN THEIR AS TIED POSITIONS FOR MARKING TRUE LINE. TRUE LINE WAS MARKED WITH RED PAINTED BLAZES, RED FLAGGING AND 5-1/2' GALVANIZED STEEL POSTS SET AT AN AVERAGE INTERVAL OF 200'.

THE BASIS OF BEARING FOR THIS SURVEY IS AS NOTED HEREON.

THIS SURVEY WAS PERFORMED USING A NIKON TOTAL STATION.

FILED

DATE: 4-2-2014 BY: JC
 THIS SURVEY CONSISTS OF:
 MAP: CS 65/81-9
 NARRATIVE:
 CORNER RPT: CS 65/76-27
 DOUGLAS COUNTY
 SURVEYOR CS 65/76-29

