

USDA-FOREST SERVICE

Index

CORNER RECORD (SEARCH)

File No. R-6 PROJ. NO. ELK CORNER W 1/16
 TOWNS. 31 S RANGE 1 W R.D. TILLER COUNTY DOUGLAS GCDB# 220300
 MERID. W.M. FOREST UMPQUA STATE OREGON

<p>CORNER DIAGRAM</p>	<p>DESCRIBE CORNER MONUMENT FOUND</p> <p>FOUND 3" BRASS CAP ON 2-1/2" IRON PIPE, FLUSH IN A MOUND OF STONE</p> <hr/> <p>DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND</p> <table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>DIA</th> <th>TYPE</th> <th>BEARS</th> <th>DIST</th> <th>FACE/MARKINGS</th> </tr> </thead> <tbody> <tr> <td>21"</td> <td>FIR</td> <td>N10°30'E</td> <td>52.8 FT</td> <td>HEALED DOUBLE BLAZE</td> </tr> <tr> <td>16"</td> <td>ROOT HOLE</td> <td>S27°W</td> <td>40.5 FT</td> <td>ROOT HOLE, 16" CEDAR WINDFALL LOG ALONGSIDE WITH HEALED DOUBLE BLAZE</td> </tr> </tbody> </table>	DIA	TYPE	BEARS	DIST	FACE/MARKINGS	21"	FIR	N10°30'E	52.8 FT	HEALED DOUBLE BLAZE	16"	ROOT HOLE	S27°W	40.5 FT	ROOT HOLE, 16" CEDAR WINDFALL LOG ALONGSIDE WITH HEALED DOUBLE BLAZE
DIA	TYPE	BEARS	DIST	FACE/MARKINGS												
21"	FIR	N10°30'E	52.8 FT	HEALED DOUBLE BLAZE												
16"	ROOT HOLE	S27°W	40.5 FT	ROOT HOLE, 16" CEDAR WINDFALL LOG ALONGSIDE WITH HEALED DOUBLE BLAZE												
<p>Obj. Ident. _____ Ident. By _____ Signature _____</p>	<p>DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER</p> <p>CORNER FALLS ON SOUTH SLOPE, IN A FENCE LINE, FROM HIGHWAY TAKE FS ROAD 1610-300 TO SECOND MAJOR SWITCHBACK, THEN FOLLOW CREEK NORTHERLY TO FENCE AND CORNER.</p>															
<p>PLANE COORDINATE POSITION DATA</p> <p>State _____ Zone _____ North _____ West _____ Estab. By _____</p>	<p>Signature _____ Title _____ Division _____ Headquarters _____</p>															

CORNER RECORD (PERPETUATION)

<p>MONUMENT : DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT</p> <p>BRUSH CLEARED AROUND MONUMENT AND TO BT'S "LAND LINE" FLAGGING TIED ON MONUMENT AND GUARD POSTS</p>	<div style="border: 1px solid black; padding: 5px; margin-bottom: 10px;"> <p>REGISTERED PROFESSIONAL LAND SURVEYOR</p> </div> <p style="font-size: 1.2em; font-family: cursive;">John Ransom</p> <div style="border: 1px solid black; padding: 5px; margin-top: 10px;"> <p>OREGON JULY 21, 1992 JOHN C. RANSOM 2561</p> </div>
--	--

ACCESSORIES : DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

MARKED: A 12" FIR BEARS, S76°15'W - 39.0 FT, MARKED "W1/16 S29" "BT" ON A DOUBLE BLAZE, WITH BRASS WASHER MARKED "LS2561" IN LOWER BLAZE BETWEEN B & T.

RED PAINT APPLIED TO BT FACES AND A 6" BAND AT HEAD HEIGHT, BT'S INCLUDE BT & SURVEY MONUMENT TAGS

DONE BY: Jonathan Drew TITLE _____ LSIT _____ DATE 1/16/2014 PLS NO./AGENCY/STATE _____
 Certified Cor. Record Prepared? YES Filed At: DOUGLAS CO. DATE _____

REMARKS

MEASURMENTS TO ACCESSORIES MADE WITH A LEICA 1103+ TOTAL STATION WITH REFLECTORLESS EDM TO ALUMINUM NAIL SET AT SIDE CENTER, BASIS OF BEARING IS MEAN GEODETIC BEARING BASED ON GPS CONTROL, MEASURE S89°29'07"E - 1346.46' TO 1/4 S29&20, MEASURE S89°38'59"E - 1330.92' 1/4 TO EAST 1/16 MAINTAINED PROPERTY LINE SOUTH 1/4 AND EAST 1/2 MILE

Index File No R-6 T. 31 S R. 1 W M. W.M. Proj No. ELK Cor. W 1/16

C.S. File No 65/85-2