

USDA-FOREST SERVICE

Index

CORNER RECORD (SEARCH)

File No. P-11 PROJ. NO. ELK CORNER C1/4
 TOWNS. 31 S RANGE 1 W R.D. TILLER COUNTY DOUGLAS GCDB# 340340
 MERID. WM FOREST UMPQUA STATE OREGON

| <p>CORNER DIAGRAM</p> | <p>DESCRIBE CORNER MONUMENT FOUND</p> <p>FOUND 3" BRASS CAP ON 2-1/2" IRON PIPE, PROJECTING 15 INCHES ABOVE A MOUND OF STONE.</p> <p>DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND</p> <table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>DIA</th> <th>TYPE</th> <th>BEARS</th> <th>DIST</th> <th>FACE/MARKINGS</th> </tr> </thead> <tbody> <tr> <td>22"</td> <td>D. FIR</td> <td>(S45W)</td> <td>(9.4 FT)</td> <td>HEALED DOUBLE BLAZE</td> </tr> <tr> <td>18"</td> <td>D. FIR</td> <td>(N34E)</td> <td>(8.9 FT)</td> <td>HEALED DOUBLE BLAZE</td> </tr> </tbody> </table> <p style="text-align: center;">REGISTERED PROFESSIONAL LAND SURVEYOR</p> <p style="text-align: center;"><i>John Ransom</i></p> <p style="text-align: right;">() = RECORD PER M70-28</p> <p style="text-align: center;">OREGON JULY 21, 1902 JOHN C. RANSOM</p> | DIA | TYPE | BEARS | DIST | FACE/MARKINGS | 22" | D. FIR | (S45W) | (9.4 FT) | HEALED DOUBLE BLAZE | 18" | D. FIR | (N34E) | (8.9 FT) | HEALED DOUBLE BLAZE |
|---|---|--------|----------|---------------------|------|---------------|-----|--------|--------|----------|---------------------|-----|--------|--------|----------|---------------------|
| DIA | TYPE | BEARS | DIST | FACE/MARKINGS | | | | | | | | | | | | |
| 22" | D. FIR | (S45W) | (9.4 FT) | HEALED DOUBLE BLAZE | | | | | | | | | | | | |
| 18" | D. FIR | (N34E) | (8.9 FT) | HEALED DOUBLE BLAZE | | | | | | | | | | | | |
| <p>Obj. Ident. _____</p> <p>Ident. By _____</p> <p style="text-align: center;">Signature _____</p> | <p>DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER</p> <p>CORNER FALLS NEAR TOP OF A STEEP SOUTH SLOPE, IN TIMBER ON SOUTH EDGE OF ROCKY MEADOW, TO ACCESS CORNER FOLLOW 1610-370 ROAD TO SPUR ON LEFT, FOLLOW 1610-375 TO SMALL CLOSED ROAD ON LEFT, FOLLOW CLOSED ROAD TO LANDING AT END, GO WEST TO POSTED PROERTY LINE, FOLLOW LINE APPROX 1000 FT NORTH TO CORNER.</p> | | | | | | | | | | | | | | | |
| <p>PLANE COORDINATE POSITION DATA</p> <p>State _____ Zone _____</p> <p>North _____</p> <p>West _____</p> <p>Estab. By _____</p> <p style="text-align: center;">Signature _____</p> | <p>Title _____</p> <p>Division _____</p> <p>Headquarters _____</p> <p>Date _____</p> <p style="text-align: right;">7100-52 (3/68)</p> | | | | | | | | | | | | | | | |

CORNER RECORD (PERPETUATION)

MONUMENT : DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT

FOUND MONUMENT LOOSE AND LEANING SOUTH IN LOOSE MOUND OF STONE, REPACK STONE AND STAIGHTEN PIPE. BRUSH CLEARED AROUND MONUMENT AND TO BT'S "LAND LINE" FLAGGING TIED ON MONUMENT AND GUARD POSTS

ACCESSORIES : DESCRIBE NEW BT's WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

NO NEW ACCESSORIES ADDED
 NEW NAILS IN BT TAGS AND PAINTED FACES & 6 INCH BAND AT HEAD HEIGHT

DONE BY: Jonathan Drew TITLE LSIT DATE 11/25/2013 PLS NO./AGENCY/STATE JOHN RANSOM, PLS2561

Certified Cor. Record Prepared? NO Filed At: _____ DATE _____

REMARKS

PROPERTY LINE MAINTINED SOUTH 1 MILE

Index File No P-11 T. 31 S R. 1 W M. WM Proj No. ELK Cor. C1/4