

FIRST RE-ESTABLISHMENT

GCDB 240700

Quarter corner common to Sec. 32, Twp. 29 South and Sec. 5, Twp. 30 South, Range 4 East,
W.M. $V=19\frac{1}{2}^\circ$

From the following evidence, set a 1x36 ins. (2.5x91 cm) G.I. pipe, flush, with 2½ ins. (6.4 cm)
bronze disc mkd:

Jackson County 1976
T29S
¼ S32 WC
—
S 5
T30S
R4E

FILED
Date: 4/7/2015 By: JC
This survey consists of:
Map: DOWN LOADED FROM JACKSON
Narrative: CO. WEBSITE 4/6/2015
Corner Rpt: CS 65/87-40
DOUGLAS COUNTY
SURVEYOR

from which:

The original B.T., 30 ins. (76 cm) Pine with "WC ¼ S 32 B" scribe visible bears record
N83°E, 7.3 ft. (2.23 m) to center of tree.

D. Fir, 21 ins. (53 cm) dia., recently mkd. "¼ S 5 RBT" in lower blaze by U.S. Forest
Service, and which I mkd. "CS" in upper blaze, bears S69°W, 73.8 ft. (22.49 m) to center
of tree at lower blaze.

P. Pine, 16 ins. (41 cm) dia., which I mkd. "CS" "BT" bears N21°E, 51.2 ft. (15.61 m) to
center of tree at lower blaze.

The witness corner lies about 30 ft. (9 m) West of the centerline of Road No. 3025 and
150 ft. (46 m) North of a creek.

Oct. 15, 1976

R. Roberts

T. Newcomb, U.S.F.S.

H. Center, U.S..F.S.

Approved By: Ed McGinty

Co. Surveyor

SEE NEXT PAGE FOR 2ND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 240700

Quarter corner common to Section 32, Township 29 South, and Section 5 Township 30 South, Range 4 East, W.M.

Found at the corner position, flush, the 1 in. diam. galv. iron pipe with a 2½ ins. diam. brass cap set on 1st Re-establishment in 1976, marked:

Jackson County 1976
T29S
S32
¼ W.C.
S5
T30S
R4E

Single remaining original bearing tree recorded by Herbert Raymond of the GLO in 1928, a fir snag with an opened single blaze revealing scribe marks "WC ¼ S 32B" brs. record; S 83° E, 7.3 ft. to center at base.

A USFS bearing tree, a D. fir, now 33 ins. diam. with a healed single blaze brs. record; S 69° W, 73.8 ft. to center at base.

Bearing tree recorded on 1st Re-establishment in 1976, a p. pine, now 20 ins. diam. with healed double blazes brs. N 23° E, 51.2 ft. Record; N 21° to center at lower blaze.

Mark new bearing trees "CS" "BT" and take measurements to center of trees at lower blaze:

Lodgepole pine 7 ins. diam. brs. N 10° W, 17.5 ft.

Lodgepole pine 11 ins. diam. brs. S 19° E, 58.2 ft.

Corner lies approx. 30 ft. west of gravel road and approx. 150 ft. north of Crater Creek.

July 25, 2007

H. Durkee

Roger R. Roberts

P. - 174

B. Beeman

Jackson County Surveyor

V. - 19°15'