

FILED

Date: 4/7/2015 By: JC  
This survey consists of:  
Map: DOWN LOADED FROM JACKSON  
Narrative: CO. WEBSITE 4/6/2015  
Corner Rpt: CS 65/87-41

DOUGLAS COUNTY  
SURVEYOR

**SECOND RE-ESTABLISHMENT**

GCDB 640700

Quarter corner common to Section 36, Township 29 South, and Section 1, Township 30 South, Range 4 East, W.M.

Found at the corner position, exposed 8 ins., the 1 in. diam. galv. iron pipe with a 2½ ins. brass cap set by the GLO in 1929, marked:

S36  
¼—  
S1  
1929

Original bearing trees recorded by H. Raymond of the GLO in 1929, found with healed blazes and measured to center of trees at base:

Fir snag brs. record; S 8° W, 27.1 ft.

Shasta fir, now 43 ins. diam. brs. record; N 23° W, 32.3 ft.

Mark new bearing trees "CS" "BT" and take measurements to center of trees at lower blaze:

Shasta fir 10 ins. diam. brs. S 50¾° W, 13.2 ft.

Shasta fir 6 ins. diam. brs. N 39¼° E, 9.2 ft.

W. fir 9 ins. diam. brs. S 25° E, 25.1 ft.

Corner lies approx. 300 ft. east of spur road.

August 13, 2008

H. Durkee

B. Beeman

Roger R. Roberts

Jackson County Surveyor

P. – 163

V. – 15°45'

C.S. FILE 65/87-41