

September 20, 1962

FILED 10-186

Date: 8/24/2015 By: SC
This survey consists of:
Map: _____
Narrative: _____
Corner Rpt: CS 65/91-3

Coes County Surveyor
Cougville, Oregon

DOUGLAS COUNTY
SURVEYOR

Dear Sir:

The following notes describe the establishment of new bearing trees at the $\frac{1}{4}$ corner between Sections 15 and 16, T26S R9W, W. M., Coes County, Oregon:

I find the 28" Fir Bearing tree, S 72° E 14.5 feet, now down, the scribe is plainly visible.

I also find the Fir Bearing tree, N 52° 30' W 21.0 feet, now a short stub with no visible marks.

From a 2" aluminium pipe which I set in place, I scribed the following:

A 28" Hemlock N 50° W 52.8 feet scribed $\frac{1}{4}$ S 16 B.T.

A 24" Hemlock N 22° E 25.3 feet scribed $\frac{1}{4}$ S 15 B.T.

Respectfully submitted for record,

MENASHA CORPORATION

Theodore S. Ellingsen

Theodore S. Ellingsen

TSE:rd

FILED
JAN 17 1963
J. E. LaTzlamme
COUNTY SURVEYOR
DEPUTY

REGISTERED
OREGON
LAND SURVEYOR
J. E. LaTzlamme
OCT. 22, 1954
THEODORE S. ELLINGSEN
329

C.S. File No 65/91-3

FLED
 Date: 8/26/2015 By: JC
 This survey consists of:
 Map: _____
 Narrative: _____
 Corner Rpt: 65/91-3

**DOUGLAS COUNTY
SURVEYOR**

GCDB INDEX : 400440		HISTORY OF CORNER				7/2/2015		
CS INDEX : k-13 T 26 R 9 16/15 Douglas County								
431832.1235 1234551.4339 1500.00 4 16								
YEAR	SURVEY REFERENCE	SURVEYOR/ CLIENT	MONUMENT FOUND	MONUMENT SET	N. E. BTS:	S. E. BTS:	S. W. BTS:	N. W. BTS:
1897	G15/22	Meldrum		Fir post 3' long 3" square and 24" into the ground		20" Fir S 72° E 21=13.86'		30" Fir N 52° 30' W 31=20.46'
1962	10/180	Ellingsen		2" Aluminum pipe	NEW: 24" Hemlock N 22° E 25.3'	28" Fir downed S 72° E 14.5'		Fir stub N 52° 30' W 21' NEW: 28" Hemlock N 50° W 52.8'
2015	26/130	Hostetter		5/8" X 36" Iron rod with aluminum cap marked T26S R9W S15 S16 ¼ LS 1975 2015	28" Hemlock stump N22°00'E 25.3' to center New: 13" Fir N17°15'E 17.1' to spike Scribed S15 ¼ BT BT Tag New: 14" Fir N86°04'E 6.0' to spike Scribed S15 ¼ BT BT Tag	Unrecorded 44" Fir Stump S15°18'E 21.8' Weyco Tag & W nail New: 15" Fir S33°54'E 10.3' to spike Scribed S15 ¼ BT BT Tag	New: 8" Double Alder S56°08'W 14.4' to spike Scribed S16 ¼ BT BT Tag	

C.S. File No 65/91-3