

FRED

Date: 5/26/2016 By: J  
This survey consists of:  
Map: CS 65/92-7  
Narrative: \_\_\_\_\_  
Corner Rpt: CS 65/93-2 thru 5

DOUGLAS COUNTY  
SURVEYOR

FENCE THIN LAND LINE #2  
RECORD OF SURVEY FOR THE  
SIUSLAW NATIONAL FOREST  
IN THE NE 1/4 SECTION 8 & NW 1/4 SECTION 9  
T.20S., R.11W., W.M.  
DOUGLAS COUNTY, OREGON  
MARCH 21, 2016

N  
BASIS OF BEARING: MEAN GEODETIC  
MAGNETIC DECLINATION: 15°22' EAST

**NARRATIVE**

THE PURPOSE OF THIS SURVEY WAS TO MARK, BY BRUSHING/BLAZING AND POSTING, CERTAIN NFSL PROPERTY BOUNDARY LINES WHICH ARE CONTROLLED BY EXISTING MONUMENTS AS SHOWN. THIS SURVEY WAS PERFORMED WITH A LEICA TCRA 1103+ TOTAL STATION & TRIMBLE R6-2 RTK GPS SYSTEM. A CLOSED TRAVERSE WAS RUN CLOSE TO TRUE LINE AND GPS CONTROL WAS ESTABLISHED ON BOTH ENDS OF THE SURVEY. ALL MEASUREMENTS WERE INCLUDED IN A LEAST SQUARES NETWORK ADJUSTMENT. PERPENDICULAR OFFSETS WERE PULLED TO SET 6 FT ALUMINUM POSTS WITH PROPERTY BOUNDARY SIGNS ALONG THE TRUE LINE AT INTERVALS NO MORE THAN 200 FT TO ACHIEVE LINE OF SIGHT BETWEEN POSTS. THE LINE BETWEEN SECTIONS 5 & 8 WAS PREVIOUSLY POSTED BY G.K. ATTIG IN 1982, CARSONITE POSTS FROM THAT SURVEY WERE TIED AND MOVED TO LINE WHERE NEEDED AND BROKEN POSTS WERE REPLACED. THE LINE BETWEEN SECTIONS 4 & 9 WAS PREVIOUSLY POSTED BY R.E. STUNTZNER IN 1975, NEARLY ALL OF THE GARDEN STYLE FENCE POSTS FROM THAT SURVEY HAVE RUSTED OFF AND BROKEN, ALL STANDING POSTS WERE REPLACED. BEARINGS IN THIS SURVEY ARE MEAN GEODETIC AND DISTANCES ARE INTERNATIONAL FEET AT GROUND. A DETAILED CORNER INVESTIGATION REPORT WAS RECORDED AT DCSO AS REFERENCED FOR EACH CORNER FOUND OR SET IN THIS SURVEY.

FOUND BC/IP WITH  
ACCESSORIES PER  
CS# 65/95-3.

PRIVATE

PRIVATE

FOUND BC/IP WITH  
ACCESSORIES PER  
CS# 65/93-5.

N89°55'08"E - 2616.29 FT  
(N89°58'06"E - 2616.25 FT)1987  
(N89°53'18"E - 2615.12 FT)1982  
(N89°43'W - 2623.50 FT)1892

FOUND MONUMENT  
WITH ACCESSORIES  
PER CS# 65/93-4.

SET MONUMENT  
WITH ACCESSORIES  
PER CS# 65/93-2.

N84°58'31"E - 2646.41 FT  
(N84°31'27"E - 2645.37 FT)1975  
(S89°40'E - 2658.48 FT)1892

S5  
S8 1/4

N89°56'14"E - 1962.24 FT  
(N89°58'06"E - 1962.19 FT)1987

NFSL

EE 1/64  
N89°51'48"E - 654.06 FT  
(N89°58'06"E - 654.06 FT)1987

S5/S4  
S8/S9

NFSL

1/4  
S4  
S9

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Jonathan B. Drew II*  
OREGON  
DECEMBER 3, 2014  
JONATHAN B. DREW II  
89396

EXPIRES: 12/31/2017

**LEGEND**

- POSTED TRUE LINE
- FOUND MONUMENT
- SET MONUMENT (SEE NARRATIVE)
- SET/FOUND BOUNDARY POST
- BC/IP BRASS CAP/IRON PIPE
- NFSL NATIONAL FOREST SYSTEM LANDS
- DCSO DOUGLAS COUNTY SURVEYORS OFFICE

**HISTORY OF SURVEYS**

1892 - W.M. THIEL, US DEPUTY SURVEYOR, UNDER CONTRACT # 567, ORIGINAL SUBDIVISION OF T.20S. R.11W..  
1975 - R.E. STUNTZNER, PE 6245, IN M55-76, SUBDIVIDES SECTION 9.  
1982 - G.K. ATTIG, PLS 1121, IN M91-20, SUBDIVIDES SECTION 8.  
1987 - DANIEL W. BAKER, PLS 1978, IN M105-40, SUBDIVIDES SECTION 5.  
NOTE: ONLY RECORDS WITH LINE RETRACEMENT DATA ARE LISTED HERE, FOR MORE DETAILED HISTORY INFORMATION ON EACH CORNER SEE THE DOCUMENTS CITED HEREON AND FILED AT DCSO.

0 FT 400 FT  
SCALE: 1" = 400 FT

I, JONATHAN B. DREW II, A REGISTERED LAND SURVEYOR IN THE STATE OF OREGON, HEREBY CERTIFY THAT THIS PLAT AND THE NOTES HEREON ARE A TRUE AND CORRECT REPRESENTATION OF A SURVEY I PERFORMED IN MARCH & APRIL 2016, AT THE REQUEST OF THE USDA FOREST SERVICE, IN ACCORDANCE WITH THE STATUTES OF THE STATE OF OREGON AND THE BLM MANUAL OF SURVEYING INSTRUCTIONS, 2009.

*Jonathan B. Drew II*  
JONATHAN B. DREW II, PLS  
USDA FOREST SERVICE  
3106 PIERCE PARKWAY, SUITE D  
SPRINGFIELD, OR 97477  
(541)-225-6474

REVIEWED BY

*John Ranson* 5/4/2016  
SIGNATURE DATE

I CERTIFY THAT THIS SURVEY WAS PERFORMED AT THE REQUEST OF THE SIUSLAW NATIONAL FOREST SUPERVISOR

*William E. Galt* 5/10/16  
SIGNATURE DATE

C.S. File No 65/92-7