

FILED

Date: 7/27/16 By: JC

This survey consists of:

Map: \_\_\_\_\_

Narrative: \_\_\_\_\_

Corner Rpt: C.S. 65/93-25

DOUGLAS COUNTY  
SURVEYOR

CORNER REPORT FORM

Section 30 Township 24 S Range 6 W  
Douglas County Date July 21, 2016  
PLSS Number 200240

CORNER DESIGNATION

1/4 corner common to  
Sections 29 and 30

- \_\_\_ Condition Report only
- \_\_\_ Not Found
- X Renewed
- \_\_\_ Unrecorded
- \_\_\_ Surveyed In
- \_\_\_ Referenced out

Previous Renewals/Surveys, etc:

Set on April 7, 1853 by Elder & Gile.  
Renewed by James Byron, Deputy Douglas County Surveyor April 18, 1958.

Monument(s) & Accessories Found: (Condition and Source)

Found standard D.C.S. brass capped iron pipe from 1958 renewal.  
1958 B.T.'s: 19" Fir with healed blazes and tag bears N 65° E, 16.4'  
The N 84° W Fir is a stump.

Bearing Trees found with 2003 D.C.S. tags and healed blazes not of record:

- A 12" diam. Fir bears S 20° W, 14.3 feet.
- A 16" diam. Fir bears S 77° W, 28.8 feet.

The 1958 D.C.S. Fir stump is 18" in diam. and 12.0' distant from the brass cap.

Monument Detail

Sketch

Standard D.C.S. brass capped iron pipe.

Monument Set (Procedures and Description)

N/A

New Accessories

Set a 6 foot steel post 2 feet West.

Surveyor's Seal

Location & Comments

Compass Declination 15° East  
Firm/Agency: David Edwards Land Surveying  
Address: P.O. Box 361  
Oakland, Oregon 97462  
Party Chief: Brant Miller  
Notes: \_\_\_\_\_  
Witness: Eric Sprinkle



Renews 12/31/17

C.S. File 65/93-25