

GOVERNMENT CORNER RESTORATION FORM

Date: 12-31-1998 By: JC

Township 30S Range 5W Sec. 7

County DOUGLAS This survey consists of:

State OR Date 12-15-98

No. \_\_\_\_\_ Narrative: \_\_\_\_\_

Corner Rpt: 66/A-10

Corner Designation

SE COR  
DLC 41

- DOUGLAS COUNTY
- Condition: Report Only
- Not Found
- Renewed
- Unrecorded
- Surveyed In
- Referenced Out

Previous Renewals 1959, 1975 DEC 30

Monument(s) Found: (Condition and Source)

3 1/2" DIA BRASS SET IN CONCRETE  
FLUSH WITH PAVEMENT (1959)

NOTIFY COUNTY SURVEYOR  
T30S

SE  
DLC  
R5W 41

1959  
BEFORE DISTURBING

Accessories Found:

PK/NAIL SET IN CONCRETE REMAINING WITH  
3 FT ABOVE GROUND, BEARS S77°E, 121.5 FT  
(AGREES WITH REC.) (1975)  
1" I.P. FOUND 6" BELOW GROUND, BEARS S79°E  
84.5 FT AGREES WITH REC. (1975) I.P. IS  
AT STATION POC 227+40 9x9 WHITE WOODEN  
POST 1 FT NORTH OF I.P.

RENEWAL

Monument Set (Procedure and Description)

Monument Detail

NONE

N/A

- HIGHEST TOP OF FIRE HYD.  
BEARS N78 1/2° E 281.0 FT

New Accessories

- 5/8" I.R. SET IN CONCRETE IS FOUND 1 FT BELOW GROUND IN  
SHRW BEARS S1° E, 265.4 FT

- SET 5/8" X 30" LONG I.R. FLUSH WITH GROUND BEARS S51 1/2° W  
207.5 FT

- 13" DIA B. OAK DOUBLE BLAZED AND SCRIBED "SE DLC 41 CS BT"  
BEARS N90° W, 110.0 FT

Sketch of Monument, Accessories, and General Area

Location & Comments

AFTER CONSTRUCTION  
IS FINISHED ASSESS  
AREA AND RESET  
DLC CORNER AND  
REFERENCE'S AS NECESSARY

Comp. Declin. 17 3/4° E  
Agency DCSO  
Party Chief RANDALL W SMITH  
Notekeeper STEPHEN J FRAISE  
Witnesses [Signature]

Address

Surveyor's Seal

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

Randall W Smith  
LARS 6-30-2001

OREGON  
JULY 25, 1990  
RANDALL W. SMITH  
2469

