

GOVERNMENT CORNER RESTORATION FORM

Date: 11-4-1999 By: X

This survey consists of:

Township 26S Range 3W Sec. 3 County DOUGLAS Map: _____

State OR Date 8-25-99 No. 400600-011 Narrative: _____

Corner Rpt: 66/12-34

Corner Designation

S4 | S3
S9 | S10

DOUGLAS COUNTY

SURVEYOR

Condition Report Only

Not Found

Renewed

Unrecorded

Surveyed In

Referenced Out

MONUMENT DETAIL

Previous Renewals 1877 + 1924 GLO, 1966 DCSO

Monument(s) Found: (Condition and Source)

2 1/2" DIA. GLO BRASS CAP
ON A 2" O.D. IRON PIPE
PROTRUDES 12" ABOVE GROUND
1929

U. S. GENERAL LAND

T26S R3W

S4 | S3
S9 | S10

1924

OFFICE SURVEY

Accessories Found:

14" NOW 26" DIA 2 FT HIGH OAK STUMP WITH
ILLEGIBLE REVERSE SCRIBING VISIBLE, BEARS
N 28° W, 13.2 FT (AGREES WITH REC.) ORT

8" NOW 20" DIA 1 FT HIGH ROTTED OAK STUMP
WITH AXE MARK, BEARS S 45° W 3.3 FT,
(AGREES WITH REC.), ORT

5" NOW 8" DIA. W. OAK WITH A FULLY HEALED
BLAZE, BEARS N 24° W 1.3 FT (AGREES WITH REC.)
1924

14" NOW DOWN AND ROTTED D. FIR PUSHED OUT OF
POSITION (REC. N 38° E 18.4 FT) 1966

12" NOW ROTTED TO GROUND ^{D. FIR} SCRIBING VISIBLE
"10 T26S R3W" BEARS S 70° E, 6.4 FT
(AGREES WITH REC.) 1966

RENEWAL

Monument Set (Procedure and Description)

NONE

Monument Detail

N/A

New Accessories

12" DIA. PINE DOUBLE BLAZED AND SCRIBED "T26S R3W S10 CS BT"
BEARS S13 1/2° E, 32.6 FT

12" DIA. D. FIR DOUBLE BLAZED AND SCRIBED "T26S R3W S9 CS BT"
BEARS S70° W 57.8 FT

10" DIA. PINE DOUBLE BLAZED AND SCRIBED "T26S R3W S3 CS BT"
BEARS N74 1/2° E, 44.8 FT

Sketch of Monument, Accessories, and General Area

Location & Comments

WHERE DIRT ROAD
CRIST OVER RIDGE
CORNER BEARS N70° E
100' ±

Comp. Declin. 17 3/4° E

Agency DCSO

Party Chief RANDALL W. SMITH

Notekeeper [Signature]

Witnesses STEPHEN J. FLAUS

Address

Surveyor's Seal

REGISTERED
PROFESSIONAL
LAND SURVEYOR

[Signature]
EXPIRES 6-30-2000

OREGON
JULY 25, 1989
RANDALL W. SMITH
2489

