

FND OK 7/29/99

TOWNSHIP 26 RANGE 06 POINT IDENTIFIER # 300140

03

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 32 and 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Addison R. Flint, Under Contract #55, dated March 1855 (DCSO records Volume 10 Pages 4358-59)

Set $\frac{1}{4}$ sec. post, from which
 A B.Oak 8" dia., bears N.69°W., 596 lks. dist.
 A Pine 36" dia., bears S.78°E., 226 lks. dist.

J.W. Cole, Deputy - L.H. Smick; Floyd Watson; Set Mathews For: Lexington Invest. Co. (Walter Hamilton) June 6, 1921 Volume 3 Page 95 - Field Book 51 Page 32

Renewed from original BTs, both alive and standing.
 Set a Rock, 8 x 8 x 24" marked $\frac{1}{4}$ S CS, from which
 48" Pine S.78°E., 149.2 ft.
 B.Oak 14", bearing scars, N.70°W., 398.2 ft.
 Erected mound of rock.

Doug. County Surveyors Office - Vernon Tracy; Mike Stone; J. Layne; Jack Heritage - Feb. 1966 C.S. File 54/7

Found - Basalt stone 8 x 9 x 24", firmly set in mound of stone.
 Orig. 36" now 60" Pine S.78°E., 149.2 ft., burned snag, open, badly rotted, no scribe found.
 Possibly bark scribed.
 No trace of B.Oak to NW.
 Set Brass cap in place of stone 12" in ground & build mound of stone around pipe & mkd: County Surveyor Office, 1966
 T26S R3W $\frac{1}{4}$ S32|S33
 New BTs - 10" Cedar S.47°W., 29.1 ft. mkd: $\frac{1}{4}$ S32 CS BT.
 12" Pine S.34°E., 6.8 ft. mkd: $\frac{1}{4}$ S33 CS BT.

FILED

Found OK, D. Bentz, January 1989, M 107-46

Date: 11-24/99 By: J

This survey consists of:

Map: _____

Narrative: _____

Corner B.M. 66/12-43