

T32S R6W SEC. COR S.23, S.24, S.25 AND S.26
RANDALL W. SMITH, STEPHEN J. FLAUSE 12-15-99
22" NOW 38" DIA. P. PINE, SHOWING EVIDENCE OF A PREVIOUS
SEARCH, WE WENT FURTHER AND FIND SCRIBING "T" AND
CHAINING NOTCH, BEARS N43°E, 9.3 FT OBT
12" NOW 18" DIA 4 FT HIGH BROKEN ROTTED OAK SNAG
BEARS S50°E, 11.2 FT OBT
10" NOW 16" DIA B.OAK WE OPEN AND FIND SCRIBING "R"

BEARS N59°W, 17.2 FT OBT
1992 BLM BRASS CAP IRON PIPE MARKED
BEARS N15 1/2° W, 20.3 FT

T32S R6W
523 524
526 525
1992

22" DIA. D. FIR SINGLE BLAZED AND SCRIBED
"T32S R6W S25 CS BT" BEARS S78 1/2° E, 22.4 FT.
RA11 DIA. ICEDAR DOUBLE BLAZED AND SCRIBED
"T32S R6W S26 CS BT" BEARS S48° W, 29.5 FT.

NOTE NW ORIG BT IS A 1951 SW BT TO 1951 COR.
SET 2 3/8" BRASS CAP ON A 1 3/8" O.D BY 32" LONG IRON PIPE
POSITION DETERMINED FROM OBT'S. PROTRUDES 9"

ABOVE GROUND

DOUGLAS COUNTY SURVEYORS

T32S R
523 524 R
526 525 W
1992
OFFICE

C.S. File No. 66/L3-8

FILED

Date: 12-21-1999 **By:** JC

This survey consists of:

Map: _____

Narrative: _____

Corner Ppt: 66/13-8

**DOUGLAS COUNTY
SURVEYOR**