

11-17-1999
T285 RAW S6 CNY16 RANDALL W SMITH, STEPHEN J FLOUSE

LOCATED SURVEY CORNER PER VOL 2 PG 176 1913
FD 18" NOW 19" DIA 2 1/2 FT HIGH ROTTED D. FIR STUMP
SCRIBING FD. " 1/16 " BEARS N51°E 3.3 FT (1913)

18" NOW TIPPED OUT OF GROUND ROTTED D. FIR
STUMP. SCRIBING FD. " CS 1/16 SBT. ROOT
WAD BEARS N 49°20' W, 27.1 FT (1913)

SET 5/8" X 30" LONG IRON ^{RED} WITH OCSO PLASTIC
CAP FLUSH WITH GROUND

18" DIA BROKEN TOP D. FIR SINGLE BLAZED AND SCRIBED "X BT"
BEARS S 80° E, 7.9 FT

20" DIA D. FIR SINGLE BLAZED AND SCRIBED "X BT"
BEARS N 23° W, 9.7 FT

FENCE CORNER WITH FENCE LINE RUNNING
SOUTH AND WEST IS APPROX. N 74° W, 115 FT

NOTE SET IIR. AND BT'S TO PERPETUATE OLD SURVEY POINT
FROM 1913 VOL 2 PG 176 CNY16 SEC 6
BT'S SCRIBED LOW ON TRUNK

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Randall W. Smith
EXPIRES 6-30-2000

OREGON
JULY 26, 1990
RANDALL W. SMITH
2488

140660.015

C.S. File No. 66/13-12

FILED

Date: 1-6-2000 By: JC

This survey consists of:

Map: _____

Narrative: _____

Corner Rpt: 66/13-12

DOUGLAS COUNTY
SURVEYOR