

1/04 29

12247

County Surveyor's Record, Douglas County, Oregon
 27

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 28 S., R. 4 W.

CHAINS							
11.85	Ravine, drains W.; ascend 25 ft. over SW. slope.						
14.15	Spur, slopes NW.; descend 48 ft. over NW. slope.						
18.85	Spur, slopes NW.; descend 58 ft. over N. slope.						
19.75	Point for N. 1/16 sec. cor. of secs. 3 and 4. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap marked <div style="margin-left: 100px;"> <table style="border-collapse: collapse;"> <tr> <td style="padding-right: 10px;">N 1/16</td> <td style="border-left: 1px solid black; padding-left: 5px;"></td> </tr> <tr> <td style="padding-right: 10px;">S 4</td> <td style="border-left: 1px solid black; padding-left: 5px;">S 3</td> </tr> <tr> <td style="padding-right: 10px;">1958</td> <td></td> </tr> </table> </div> from which A fir, 8 ins. diam., bears S. 37° E., 54 lks. dist., marked N. 1/16 S3 BT. A fir, 7 ins. diam., bears N. 30° W., 48 lks. dist., marked N 1/16 S4 BT. Descend 144 ft. over N. slope.	N 1/16		S 4	S 3	1958	
N 1/16							
S 4	S 3						
1958							
27.40	Ravine, drains N. 70° W.; descend 24 ft. along W. slope.						
33.00	Ravine, drains N. 60° W.; ascend 82 ft. over SW. slope.						
38.65	Spur, slopes W.; descend 17 ft. along W. slope.						
41.63	The standard cor. of secs. 3, 4, 33 and 34.						

FP OK 2/16-00

35-6

31-7

N 34 W
67