

T275R4W

FILED MAR 25 2000

EAST 1/4 S. 26 ONLY

2-23-00

RANDALL W. SMITH STEPHEN J. FLAUSG

FD STONE TOP MEASURES 10"

X 8" PROTRUDES 8" OUT OF GROUND

WITH 1/4 MARKED ON NW FACE (1917)

3/4" IRON ROD SET BY DCSG IN 1965

ALONG NW SIDE OF STONE

0.6 FT. PROTRUDES 5" OUT OF
GROUND.

FROM CENTER TOP OF STONE

22" NOW BADLY ROTTED D. FIR

STUMP WITH ROTTED BLAZE, NO

SCRIBING FOUND BEARS S68°W

17.2 FT (OBT)

14" NOW ROTTED TO GROUND P. FIR

BEARS N45 1/2°W 32.3 FT (OBT)

6" NOW 9" DIA MADRONE WITH A

FULLY HEALED SINGLE BLAZE

BEARS N55°W, 31.9 FT (1963)

4" NOW 6" DIA MADRONE WITH A

FULLY HEALED SINGLE BLAZE,

BEARS N82 1/2°W, 23.0 FT

(REC N86°W 24.2 FT) (1963)

1917 BLM BC/1P W 1/4 S25 ONLY

BEARS S2°W, 27.4 FT

SEE BACK

C.S. File No. 66/14-36

NEW
16" DIA. D. FIR SINGLE
BLAZED AND SCRIBED
" $\frac{1}{4}$ SEC CS BT BEARS
N36 $\frac{1}{2}$ ° W 9.6 FT

W $\frac{1}{4}$ OF SEC 25 ONLY
FOUND OK 2-23-00

CS 66/14-36