

R02820A

PI # 200300

T235 R5W 19 20

8-28-00

FILED AUG 29 2000 30 29

RANDALL W SMITH, STEPHEN J FLAUSER
 FO 1959 36" LONG BRASS
 CAP / IRON PIPE OUT OF
 GROUND LEANING AGAINST A
 2WAY FENCE CORNER FENCE
 LINE RUN NORTH AND EAST.
 WEST SIDE OF FENCE CORNER
 ERODED AWAY FOUND
 13" X 9" X 4" STONE MARKED WITH
 A " + " ON TOP AND "30" ON
 ONE SIDE. APPROX. 10 FT ;
 SW OF FENCE CORNER IN
 ERODED DITCH (SOURCE UNKNOWN)

18" NOW 25" DIA D. FIR WITH A
 FULLY HEALED DOUBLE BLAZE
 BEARS S 85° E, 64.6 FT (1959) M
 8" NOW 15" DIA. W OAK WITH A FULLY
 HEALED DOUBLE BLAZE, BEARS
 N 60° W, 140.0 FT (1959)
 20" NOW 27" DIA. MULTI TRUNKED
 W. OAK WITH A FULLY HEALED
 DOUBLE BLAZE ON 13" DIA. WEST
 TRUNK, ROOT CROWN BEARS
 N 80° E, 83.6 FT (1959) (ON BALK)

C.S. File No. 66416

J. L. DARLING CORP
TACOMA WASH U.S.A

"Rite in the Rain"
WEATHERPROOF

No. 302

18" NW 32" DIA. WOODK SHOWING EVIDENCE OF BEING PREVIOUSLY OPENED, BEARS $S 57\frac{1}{4}^{\circ} E$ 429.0 FT (OBT)

SET A $\frac{5}{8}$ " BY 5 FT LONG IRON ROD WITH DC SO ALUM. CAP MARKED DOUGLAS CO.

PROTRUDES 4" ABOVE GROUND

1920
3029
2000

1.5 FT WEST SURVEYOR OF FENCE CORNER, AT CALL CORNER POSITION.

SET 1959 DC SO BC/IP N $75^{\circ} E$, 20.0 FT FROM CORNER. ADD MARKS $S 45^{\circ} W$ 20 FT TO COR

RESET 2000" COUNTY SURVEYORS OFFICE

PROTRUDE 5" ABOVE GROUND

T 235 R 5W
519 | 520
530 | 520

$S 45^{\circ} W$ 20 FT TO

SET STONE 1959 COR

ALONG SOUTH EDGE OF BC/IP PROTRUDES 1" ABOVE GROUND. (NOTE BC/IP AND

STONE NOW REFERENCES TO

I.R. AT CORNER) ("+" ON STONE

0.4 FT SOUTH OF BC/IP) (566/16-37