

PI # 600400

10-23-00

T30S R2W

514 | 513
523 | 524

FILED OCT 30 2000

RANDALL W. SMITH STEPHEN J. FLAUSCH
FD 1963 BLM BRASS CAP / IRON
PIPE PROTRUDES 4" OUT OF
GROUND.

- 16" NOW 20" DIA. W. OAK WITH A
FULLY HEALED DOUBLE BLAZE
BEARS N52°W, 99.2 FT (1990)

- 14" NOW 15" DIA. W. OAK WITH A
FULLY HEALED DOUBLE BLAZE,
BEARS N4°E, 46.9 FT (1990)

- 24" NOW 28" DIA 30 FT HIGH
D. FIR SNAG WITH A FULLY HEALED
SINGLE BLAZE, BEARS S75 1/2°W,
119.5 FT (1990)

- 2' X 4' X 1' HIGH SANDSTONE
OUTCROP TOP CENTER FIT'S
WITH RECORD S69 1/2°E, 46.6 FT
CHISELED "+" NOW GONE (1959)

- 24" NOW 30" DIA 8 FT HIGH
W. OAK SNAG SHOWING EVIDENCE
OF BEING PREVIOUSLY OPENED WITH
TWO ROTTED BLAZES, BEARS
N13 1/2°E, 90.2 FT (ORIG. REC.
N12°E, 92.4 FT) ORT
ON BACK

C.S. File No. 66/16-55

J. L. DARLING CORP
TACOMA WASH USA

"Rite in the Rain"
WEATHERPROOF®

No. 302

NEW

15" DIA. D. FIR DOUBLE BLAZED
AND SCRIBED " T 30 S R 2 W
S 23 C S B T" BEARS S 57° W,
100 ± FT

CORNER LIES IN OPEN FIELD
NE CORNER OF FIELD AND
3WAY FENCE CORNER. BEARS
N 38° W, 59 FT, TO FENCE
CORNER.

MOUND OF STONE SET
AROUND BASE OF BL/1P
ALONG WITH A METAL
WITNESS POST

COMPASS DEL. 17 1/2° E

CS 66/16-55