

10-31-00 FILED NOV 2 2000

①

T265 R4W SSW COR DLG43

RANDALL W SMITH

STEPHEN J FLAUSE

FO 2" WIDE BY 24" LONG

AUTO SPRING 1" BELOW

GROUND LEANING 1 FT

SE OF PLUMB (1923) SEE

CS 3/30 page 6 NOTES OF

RENEWAL "SET I.P. CAR SPRING

FOR CORNER" NOTE AS AN

IRON PIPE 1/2 X 2 X 2 FEET"

IN VOL 3 pg 223

- NO BT'S FOUND

SET 2 3/8" BRASS CAP ON A

1 3/8" O.D BY 32" LONG IRON

PIPE AT PLUMB POSITION OF

AUTO SPRING. PROTRUDS 6"

OUT OF GROUND AUTO SPRING

SET ALONG NORTH EDGE OF

BE/IP PROTRUDS 2" OUT OF

GROUND.

DOUGLAS COUNTY SURVEYORS

	T265
R	SSW
+	DLG
W	43

2000
OFFICE

CS File No. 66/18-2A

(ON BACK)

NEW

(2)

- 30" DIA PINE SINGLE BLAZED AND
SCRIBED "SSW DLC 43 CS BT"
BEARS $S 0 \frac{1}{4}^{\circ} W$, 257⁸ FT

- 31" DIA. B. OAK DOUBLE BLAZED AND
SCRIBED "SSW DLC 43 CS BT"
BEARS $S 68 \frac{1}{2}^{\circ} W$, 227³ FT

- 1" DIA AXLE SHAFT TOP LUMBS
1 FT SOUTH OF PLUMB AT AN OLD
FENCE CORNER WITH FENCE LINE
RUNNING * NLY & SWLY. PLUMB
POSITION BEARS $N 3^{\circ} E$, 568.5 FT
(PROBABLE PROPERTY CORNER SET IN
1925 AS AN I.P. $N 2^{\circ} 21' E$, 579² FT)
SEE VOL 3 PG 223 AND CS 3/20

2" WIDE AUTO SPRING PROTRUDERS
3" OUT OF GROUND, 1 FT NORTH
OF A SWLY RUNNING FENCE LINE
BEARS $N 59 \frac{1}{2}^{\circ} W$, 451.4 FT
(PROBABLE PROPERTY CORNER SET IN
1925 AS AN I.P. AUTO SPRING!
CALC. REC. $N 59 \frac{1}{2}^{\circ} W$, 456.1 FT)
SEE CS 3/20

CS 66/18-2A

③

T265 RAW SSW DCL 43

NEW

31" DIA D. FIR SINGLE BLAZED
AND SCRIBED " SSW DCL 43

CS BT" BEARS N 30 1/2° E,

225.0 FT

COMPASS DECLINATION 17 3/4° E

SET METAL WITNESS

POST + SIGN 1 FT

EAST OF CORNER

C.S. File No. 166/18-2A

CS FILE FOLDER

CONTAINS

MORE

INFORMATION