

FILED

JAN 9 2001

12-11-00

T225 R6W 1/4 S 24
S 25

040300,074

RANDALL W SMITH
STEPHEN J FLAUSCH

FD HAINES "T" IRON PROTRUDING
14" ABOVE GROUND (NO RECORD)
5/8" IRON ROD WITH YELLOW
PLASTIC CAP "BRINCH ENG 1135"
PROTRUDING 1" ABOVE GROUND
SET IN 1992 (M 116-29)
I.R. BEARS S 38 1/2° W 34.5 FT
FROM "T" IRON.

30" NOW 40" DIA 2 1/2 FT TALL
PARTIALLY ROTTED D. FIR
STUMP. SEARCHING TYPE AXE
MARKS FOUND NEAR THE
EXTERIOR OF STUMP. WE OPEN
TO 15" FROM CENTER AND
FIND BURLED WOOD AND
AN OLD BLAZE WITH FAINT
SCRIBE MARKS, A LINE
AND A PARTIAL ARC. A
GOOD CHAINING NOTCH IS
FOUND AT BOTTOM OF BLAZE.
BEARS S 4 1/4° W, 87.1 FT
FROM "T" IRON (REC S 5° W
90.4 FT) OBT

C.S. File No. 606/19-1

C

(NOTE: CORNER LIES ON A STEEP NE
SLOPE, SEE CS 49/143 REFMS)
TO 1961 CORNER SEARCH
ORIG NE BT NOT FOUND
FROM "T" IRON

NEW 7" DIA HEMLOCK (M116-29
NE BT) WITH A FULLY HEALED
DOUBLE BLAZE ON SW TRUNK
BEARS S 41 1/2° W, 7.6 FT. WE
SINGLE BLAZE FACING "T"
IRON AND SCRIBE "XCS BT"

24" DIA D. FIR (M116-29
NW BT) WITH A FULLY HEALED
SINGLE BLAZE ON SE TRUNK
BEARS N 65° W, 56.9 FT WE
SINGLE BLAZE FACING "T"
IRON AND SCRIBE "XCS BT"

24" DIA. D. FIR SINGLE
BLAZED AND SCRIBED "YAS
24 CS BT" BEARS N 55° E,
29.9 FT

WE AGREE WITH BRG'S AND
DIST. TAKEN BY KEN REIFRANE
USING EDM FOR DISTANCES,
BRG'S BASED ON GPS BT
TAG'S FACING "T" IRON WILL
HAVE SMALL DIFF. IN BRG + DIST.
FROM THIS RENEWAL RECORD

CS 66/19-1