

6-18-01 R062020C

T223 R6W NW COR QLL 38?

RANDALL W SMITH STEPHEN J FLAUSCH

FD STONE LOOSE ON TOP
OF GROUND, NO POSITION.

MEASURES 6" X 8" X 16" NO MARKS
(REC. 6" X 8" X 16") ORIG?

FD 3/4" DIA. X 13" LONG SHAFT
WITH A SMASHED TOP LOOSE ON

TOP OF GROUND NO POSITION (REC. ROD)

REC S0°22'E, 12.72' FROM STONE, VOL. 2 PG 20A

FD REMAINS OF TWO OLD

OAKS THAT BEAR N51°E, 71.3 FT

BETWEEN THEM. THEY WOULD

AGREE WELL WITH A REC. OF

N30°W, 139.3 FT TO A ROTTEN

STUMP NO MARKS FOUND AND

N4°W 167.6 FT TO A 28" DIA

OAK SNAG THAT HAS OLD FENCE

WIRE GROWN INTO IT. WE OPEN

AND FIND OLD AXE MARKS

NO SCRIBING FOUND. RECORDS

SHOW THIS - BT AS N40°W

OR N4°W.

FROM A POSITION DETERMINED

FROM POSSIBLE ORIG. BT'S

N30°W, 139.3' AND N4°W 167.6'

(ON BACK)

FILED JUL 11 2001

NO. 302

C.S. File No.

66/21-26A

②

STONE BEARS N 80° E, 16 FT
SHAFT BEARS N 50° W, 22 FT

AREA AROUND CORNER SHOWS EVIDENCE
OF BULL DOZER SCARS AND
FIELD WORK FROM YEARS PAST

A SEARCH WAS MADE FOR THE
NW CORNER OF DCC 39 FD
1/2" I.D. DRIVEN IRON PIPE
8" BELOW GROUND NO BT'S
FOUND. (REC 2" N.P. VOL 5 PG 20A)
TIE BETWEEN CORNER'S MADE
BEARS N 89° 43' E, 2227.8 FT
(STAFF COMPASS (DEC. 17 1/2° E)
(REC. S 89° 46' E, 2223.5 FT
VOL 5 PG 20A)

TO PROTECT EVIDENCE AS
FOUND A 5/8" X 30" LONG
IRON ROD WITH DCSO PLASTIC
CAP IS SET AT POSITION
AS DETERMINED BY RESIDUE
OBJ'S N 30° W, 139.3 AND
N 4° W, 167.6 FT PROTRUDES
1" ABOVE GROUND 66/21-26A

(3)

FD STONE IS PLACED ALONG
EASTERLY EDGE OF I.R.
FD SHAFT IS SET ALONG
SOUTHERLY EDGE OF I.R.
FLUSH WITH GROUND.

NW REFERENCES

30" DIA W. OAK DOUBLE BLAZED
AND SCRIBED "XCS BT", BEARS
N 72° W, 67.9 FT

21" DIA. D. FIR DOUBLE BLAZED
AND SCRIBED "XCS BT", BEARS
N 0³/₄° W, 91.0 FT

COMPASS DECL. 17¹/₂° E

C.S. File No. 66/21-26B