

6-19-01

ROG 2021A

FILED JUL 11 2001

TZRS, RW

NE COR DLC 38

RANDALL W SMITH

NW COR DLC 39

STEPHEN J FLAUSK

FD 1/2" I.D. IRON PIPE 8"

BELOW GROUND. (REC 2" I.P.

VOL 5 PG 20A) NO BT'S

FOUND. I.P. MEASURES 34"

LONG.

TIE BETWEEN THIS I.P.

AND PROBABLE POSITION OF

THE NW COR DLC 38 BEARS

S 89° 43' W 2227.8 FT

(STAFF COMPASS DECL. 17 1/2° E)

(REC. N 89° 46' W 2223.5 FT

VOL 5 PG 20A).

TIE BETWEEN THIS I.P.

AND PROBABLE POSITION OF

THE SW COR OF DLC 38

AS DETERMINED BY FOUND

I.P. BEARS S 0 1/4° W

5307.0 FT (STAFF COMPASS

DECL. 17 1/2° E) (REC SOUTH

5299.8 FT) (ORIG. DLC SURVEY)

(ON BACK G.S. File No.

66/21-27

U.S. BANKING CORP.
FARMINGTON, MICH. 48301

Register
SEALED
SEALED

NO. 302

TO PROTECT FOUND POSITION
OF I.P. WE SET I.P. AT
POSITION FOUND 8" BELOW
GROUND. A 5/8" X 30" LONG
IRON ROD IS SET ALONG
SIDE PLUMB OVER TOP, WITH
7/8" DCSO PLASTIC CAP PROTRUDING
5" ABOVE GROUND.

REFERENCES

SE CONCRETE CORNER, STEM WALL OF
FEEDER SHED, BEARS N117⁴°E, 199.2 FT

SW CONCRETE CORNER, STEM WALL OF
FEEDER SHED, BEARS N97⁴°W, 170.2 FT

12" DIA. PEAR DOUBLE BLAZED
AND SCRIBED "X CS BT"
BEARS S37°E, 280.8 FT