

9-11-01

FILED SEP 14 2001

T215 R6W 1/4 $\frac{S25}{S36}$

RANDALL SMITH STEPHEN J FLAUSCH

1" 1961 HAINES "T" IRON
WITH TOP 10" BROKEN OFF
REMAINDER IS PLUMB IN GROUND.

5" OAK NOW ROOT HOLE
BEARS N72°E, 48.6 FT
CRBC N75°E, 48.6 FT) (1961)

22" NOW 24" DIA DOWN AND
ROTTED OAK WITH BT TAG. HEALED
ROOT HOLE BEARS 571°W, ^{BLAZE}
47.6 FT (REC. 574°W, 47.6 FT) (1961)

SET A 2 3/8" DIA BRASS CAP
ON A 1 3/8" O.D. BY 32" LONG
IRON PIPE AT PLUMB POSITION
OF "T" IRON. BC/IP PROTRUDES
4" OUT OF GROUND. "T" IRON'S
SET ALONG NORTH EDGE OF
BC/IP PROTRUDES 2" OUT
OF GROUND.

DOUGLAS COUNTY SURVEYORS

T 215
1/4 $\frac{S25}{S36}$ R
2001 6
W

(BACK) C.S. File No. 66/29-6

NEW

4" DIA. D. FIR DOUBLE BLAZED
AND SCRIBED "X BT" BEARS
N 7 1/2° W, 6.8 FT

10" DIA D. FIR DOUBLE BLAZED
AND SCRIBED "Y4536 CS BT"
BEARS S 58° W, 43.8 FT
SET A METAL WITNESS
POST + SIGN 5 FT EAST
OF CORNER

NO OTHER SCRIBABLE TREES

COMPASS BEEL 17 1/2° E

66/29-6