

TZZS

R  
6  
W

1/4  
S1/56

R  
5  
W

9-29-01

FILED SEP 26 2001

RANDALL W SMITH STEPHEN J FLAUSER  
FD 1906 (SAND) STONE MONUMENT BROKEN  
IN 5 MAJOR PIECES MARKED

"1/4" ON TOP. MEASURES  
6" X 6" X 12", FOUND 2" BELOW  
GROUND. STONE FOUND

1.5 FT WEST OF OLD FENCE  
CORNER WITH OLD MOSTLY

DOWN FENCE LINES RUNNING

N-S + E 1/2" IRON PIN

PROTRUDES 3" ABOVE GROUND

BEARS 55° E, 3.1 FT FROM

STONE (1976 PROPORTIONED

POSITION) BOTH BT'S FROM

1976 FOUND IN GOOD SHAPE

NO 1855, 1906 OR 1931 BT'S

FOUND.

NOTE: POSITION OF FOUND STONE

AGREES WITH OLD FENCE LINES

BREAKS IN STONE APPEAR

TO BE FROM NATURAL CAUSES.

STONE IS ALTOGETHER IN ONE

SPOT DOES NOT APPEAR TO

HAVE BEEN DISTURBED. BOTTOM

PIECE, FIRMLY SET.

66/25-11A  
C.S. File No.

Return to the Rain  
WEATHERPROOF

No. 302

U.S. CARTRIDGE COMPANY  
FACSIMILE MARKING

SET 2 3/8" DIA BRASS CAP ON  
 A 1 3/8" O.P. BY 32" LONG  
 IRON PIPE AT POSITION OF  
 FOUND STONE PROTRUDES  
 8" OUT OF GROUND. STONE  
 SET ALONG SOUTHWEST OF  
 BC/IP FLUSH WITH GROUND.

DOUGLAS COUNTY SURVEYORS OFFICE

T225

Y4

S1 | S2

2401

BT'S FROM 1976 BRG + DIST  
 TAKEN FROM NEW BC/IP  
 8" NOW 11" DIA. B. OAK WITH  
 A FULLY HEALED BLAZE BEARS  
 N62 1/2° E 53.0 FT

12" NOW 19" DIA ALDER  
 WITH A HEALED BLAZE 6 FT  
 ABOVE GROUND ROOT CROWN  
 BEARS N 2 1/4° E, 15.7 FT

66/29-11A

NEW

15" DIA W. OAK DOUBLE  
BLAZED AND SCRIBED "1/4 S 6  
CS BT" BEARS 59°E,  
30.3 FT

9" DIA D. FIR DOUBLE  
BLAZED AND SCRIBED "1/4 S 1  
CS BT" BEARS 559°W,  
15.1 FT

COMPASS DECL. 17 1/2°E

C.S. FILE NO. 66/29-11 B