

10-3-01

FILED OCT 24 2001

T225 RTW SEC 32 SE COR DCC 37

RAMMELL W SMITH STEPHEN J FLAUSK

- FD 1" SQUARE HEAD BOLT  
 WITH A 3" DIA WASHER  
 (PROTRUDS 1" ABOVE GROUND)  
 (SOURCE UNKNOWN). (SIMILAR BOLT'S  
 SET IN 1914. VOL 5 pg 20)

- CORNER 2 1/2 FT WEST OF A NLY-SLY FENCE

- 18" DIA 33" DIA DOWN H. OAK  
 PREVIOUSLY OPENED ROTTEN BLAZE  
 WE OPEN LOWER AND FIND  
 ORIG. REVERSE SCRIBING "T"  
 APPROX 9" FROM CENTER OF TREE  
 ROOT HOLE BEARS S 8° W,  
 151.1 FT

- (HAINES 1962 M23-76 SURVEY  
 NOTES THIS BT AS HAVING BEEN  
 REDESCRIBED, 1949 D.C. ROAD 203  
 SURVEY SHOWS TIE TO DCC CORNER  
 AND THIS BT) OBT  
 ORIG. SE BT GONE  
 NEW

5/8" IRON ROD IN A TWAY FENCE  
 CORNER SET M 42-43 BEARS

S 10 1/2° W, 94.7 FT  
 (COMPASS DECL. 17 1/2° E AGROSS) 16  
 (WELL WITH M42-43) C.S. File No. 66/29-

DARLING CORNER  
OKLAHOMA WARR 1941

Site in the Rain  
FEATHERPROOF

No. 302

GPS R100320A N45°W 75'  
OFFSET TO COR.

5/8" IRON ROD SET IN M42-43  
AT A FENCE CORNER BEARS,  
N12 1/4° E, 115.1 FT

16" DIA. D. FIR DOUBLE BLAZED  
AND SCRIBED "SE D/LC 37 CS BT"  
BEARS N24 3/4° E, 83.1 FT

19" DIA. D. FIR SINGLE BLAZED  
AND SCRIBED "SE D/LC 37 CS BT"  
BEARS S30° W, 13.2 FT

13" DIA. D. FIR DOUBLE BLAZED  
AND SCRIBED "SE D/LC 37 CS BT"  
BEARS N7° W, 8.6 FT

SET A 2 3/8" DIA. BRASS CAP ON  
A 1 3/8" O.D. BY 32" LONG IRON  
PIPE AT REFERENCED POSITION OF  
BOLT. BC/IP PROTRUDES 5" ABOVE  
GROUND 29" LONG. 3/4" DIA. BOLT SET ALONG  
SOUTH EDGE OF BC/IP PROTRUDES  
3" OUT OF GROUND

DOUGLAS COUNTY SURVEYORS OFFICE

T 22 S  
SE R 7 W  
D/LC 37