

10-23-01

FILED NOV 13 2001

T22S R6W Y4S10 | S11

RANDALL W SMITH STEPHEN J FLAUSCH

FD 1961 DCSO BRASS CAP / IRON PIPE,
PROTRUDES 11" ABOVE GROUND.

ENVIRONMENT IS AT FENCE CORNER
WITH FENCE LINE RUNNING
E-W AND N.

FD 1914 3/4" I.D. IRON PIPE

FLUSH WITH GROUND 1961

DCSO BC/IP BEARS N79°W,
4.8 FT (VOLS PG 20A)

FROM 1961 BC/IP

24" NOW TRIPLE TRUNK WIDAKS
CENTER TRUNK IS DOWN 30"

DIA EASTERLY TRUNK HAS A
FULLY HEALED BLAZE, BEARS
S43°W 20.3 FT TO ROOT
CROWN (1961)

12" NOW 23" DIA W. DAK WITH
A FULLY HEALED SINGLE
BLAZE, BEARS S80°E, 144.7 FT
(REC S73°E, 144.7 FT) 1961

SET A 5/8" BY 30" LONG IRON ROD
IN MIDDLE OF FD IRON PIPE
WITH DCSO ALUM CAP STAMPED
"2001" IRON ROD PROTRUDES
6" ABOVE GROUND. IP, NOW 2" BELOW GROUND

J. L. DARLING COPY
TACOMA, WASH. 98401

Printed in the U.S.A.
REAR PROOF

No. 302

C.S. File No. 166/29-18A

COMPASS DBL 17 1/2° E

1961 DCSO BRASS CAP
SAWN OFF OF IRON PIPE
A DCSO PLASTIC CAP SET
IN CENTER NOW PROTRUDES
9" ABOVE GROUND.

1961 BT'S TIED TO 1914
CORNER

24" TRIPLE TRUNKED W. OAK
BEAMS S 45 1/2° W 92.9 FT

23" W. OAK BEAMS
S 80° E, 139.9 FT

NEW BT'S TIE TO 1914
CORNER

5" DIA. D. FIR DOUBLE BLAZED
AND SCRIBED "X BT"
BEAMS S 66° E, 3.9 FT

5" DIA D. FIR DOUBLE BLAZED
AND SCRIBED "X BT"
BEAMS S 36° W, 11.4 FT

(SEE SKETCH ATTACHED TO)
NE COR OLC 39 C.S. File No. 66/29-18B

