

T245 RAW Y4S31/S32

1-10-02

FILED JAN 23 2002

RANDALL W SMITH STEPHEN J FLAUSE
FD 14 "NOW 29" DIA ASH WE OPENED
A SMALL HOLE AND FIND GOOD
PARTIAL SCRIBING "45". AT 1963
RECORD POSITION TO CORNER, WE
FIND SMALL BROKEN PIECES OF
SAND STONE (1917) (S81°W 144.8 FT)

1-14-02

1963 SW BT GONE

ORIG. SW BT GONE

18 "NOW 32" DIA W. OAK FALLEN
ON FACE, WE DID NOT OPEN
BEARS N 84°E, 642.8 FT (AGREES
WITH 1917 REC) (ORIG. REC. S86°E,
633.6 FT) OBT

WE PERPETUATE CORNER POSITION AS
DETERMINED IN 1917, RENEWED
IN 1963 AND ACCEPTED IN 1976
M 60-70. DISTANCE TO 5 1/16 COR
BETWEEN SECTION 31 AND 32
CHECKED WELL WITH M 60-70

(NOTE: ERRORS IN BRG'S + DIST.'S
TO ORIG. BT'S FA. 1917)

(ON BACK) C.S. HIB NO. 66/32-5

(NOTE: ORIG. CALL TO STREAM IS 142'
SOUTH OF CORNER, WE FIND APPROX 70')

SET: A 2 $\frac{3}{8}$ " DIA. BRASS CAP ON A 1 $\frac{3}{8}$ "
O.A. BY 32" LONG IRON PIPE AT
RECORD POSITION FROM 1963 ASH BT.
BL/IP PROTRUDES 9" ABOVE GROUND.
(NOTE CEDAR POST FOUND IN DUG HOLE)

DOUGLAS COUNTY SURVEYORS

T24'S

¼ 531/532

RAW

2002

METAL FENCE

POST SET 1 FT

EAST OF CORNER

DOUBLE TRUNKED W. OAK DOUBLE
BLAZED AND SCRIBED "¼ 531 CS BT"
ON 12" DIA. SOUTHERLY TRUNK,
BEARS S 71 $\frac{1}{2}$ ° W, 90.5 FT

13" DIA. D. FIR DOUBLE BLAZED AND
SCRIBED "¼ 532 CS BT" BEARS
S 1 $\frac{1}{2}$ ° E, 100.3 FT

16" DIA. W. OAK SINGLE BLAZED AND
SCRIBED "¼ 531 CS BT" BEARS N 8 $\frac{3}{4}$ ° W,
260.5 FT.

CORNER LIES IN PLOWED FIELD

COMPASS DECL. 17 $\frac{1}{2}$ ° E

66/32-5