

5-30-02 615 ROG 0320A
T22S R7W Y4 S33 | S34
FILED JUN 6 2002

RANDALL W SMITH STEPHEN J FLAUSCH
FD 1961 BENTHAINES "T" IRON
PROTRUDS 4" OUT OF GROUND.

11" NW 33" DIA 1 1/2 FT HIGH
D. FIR STUMP W/8 OPEN AND
FIND GOOD SCRIBE MARK AND
BLAZE, BEARS N 49° W, 171.3 FT (1961)
12" NW 26" DIA 1 FT HIGH W/OAK
STUMP, NO MARK VISIBLE, BEARS
S 27° E 359.1 FT (1961)

NEW

- 29" DIA. D. FIR SINGLE BLAZED
AND SCRIBED "Y4 S33 CS BT"
BEARS S 78 1/4° W, 185.7 FT
- 22" DIA. D. FIR DOUBLE BLAZED
AND SCRIBED "Y4 S33 CS BT"
BEARS S 31 3/4° W, 482.0 FT
- 22" DIA W/OAK DOUBLE BLAZED
AND SCRIBED "Y4 S34 CS BT"
BEARS S 16 3/4° E, 411.8 FT

(ON BACK)

C.S. File No 66/34-S

32" DIA W. FIR DOUBLE BLADED
AND SCRIBED "1/4 534 CS BT"
BEARS $533\frac{1}{2}^{\circ}E$, 406.6 FT

COMPASS DECL. $17\frac{1}{2}^{\circ}E$

SET $\frac{5}{8}$ " BY 60" LONG IRON
ROD WITH DCSG ALUM
CAP STAMPED $\frac{1}{4}$ AT
33/34
2002

PLUMB POSITION OF MINES
"T" IRON PROTRUDES 8" ABOVE
GROUND.

METAL WIZ. POST + SIGN SET
1 FT NORTH

CORNER LIES IN OPEN FIELD
NO REASONABLE TREES TO
THE NORTH