

7-17-02

NN COR

FILED AUG 8 2002
PI 500600

T 28 S R 5 W

53 | S2

PI

RANDALL W SMITH

510 | S11

STEPHEN J FLAUSCH

1961 BE/IP AND STONES NOT FOUND
AREA AROUND CORNER BULLDOZED

ORIG 16" Y. OAK NOW ROTTEN REMAINS OF
OAK STUMP AND ROOT HOLE BEARS

S 14° 36' 40" E, 1111.5 FT (1961 REC. M 23-5)
S 14° 40' 40" E, 1111.5 FT, ORIG. REC. S 16° E, 1100.9 FT

ORIG 18" Y. OAK NOW ROTTEN REMAINS

ROE OF OAK BEARS S 10° 06' W,

933.8 FT (ORIG REC S 9° W, 953.7 FT

1961 REC S 10° 16' 40" W, 933.8 FT)

CHECKED 1961 TIE TO 1/4 ^{S2}/_{S11}

AND AGREED WITH M 23-5

SURVEY RECORD, (S 88° 42' 30" E, 2690.10 FT)

POSITION OF SECTION CORNER AS

MONUMENTED IN 1961 DETERMINED

By SURVEY M 23-5 AS SHOWN
ABOVE.

SET 2 3/8" DIA. BRASS CAP ON A

1/4" O.D BY 30" LONG IRON PIPE

PROTRUDES 7" OUT OF GROUND

"DOUGLAS CO. SURVEYORS OFFICE"

T 28 S

R 5 W

53 | S2

C.S. File No 66/34-20

510 | S11

2002

(ON BACK)

J. L. DARLING CORP.
TACOMA WASH 98404

"Rite in the Rain"
WEATHERPROOF

No. 302

COMPASS PVEL 1779°E

NEW

- 9" DIA. MAPLE WITH FENCE WIRE GROWN INTO TRUNK SINGLE BLAZED AND SCRIBED "X S11 BT" ABOVE FENCE LINE APPROX 5 1/2 FT ABOVE GROUND BEARS S49°E, 32.1 FT.
- 19" DIA. APPLE DOUBLE BLAZED AND SCRIBED "X S10 BT" BEARS S16°W, 79.2 FT
- 13" DIA. MAPLE DOUBLE BLAZED AND SCRIBED "T28S R5W S10 CS BT" BEARS S88°W, 66.1 FT
- 7" DIA. APPLE DOUBLE BLAZED AND SCRIBED "S2CS BT" BEARS N14°E, 76.5 FT

GPS

R071721A