

12-23-02

PI # 640100
FILED JAN 13 2003

T215 R12W S1/4 SEC 36

RANDALL W SMITH JOHN A. PIKE
FO 1991 BLM BRASS CAP IRON
PIPE FLUSH WITH GROUND ON STEEP
NORTH SLOPE OF RIVER BANK,
1" IRON ROD PROTRUDES 2" OUT OF
GROUND BEARS S53°W 12.1 FT
SOURCE UNKNOWN

18" NOW 38" DIA. HEMLOCK
WITH A HEALED BLAZE BEARS
S76°W 81.8 FT (1971 DCSO)

36" NOW 40" DIA SPRUCE WITH
A FULLY HEALED BLAZE BEARS
BEARS N53°W, 69.6 FT (RBC
N50°W, 69.6 FT) (1991 BLM)

DCSO 2 1/2" DIA. BRASS CAP ON A 1 1/2" O.D. BY 32" LONG IRON PIPE IS
SET ON SECTION LINE WEST 75.0 FT
FROM 1991 BLM BLM, PROTRUDES
5" OUT OF GROUND.

DOUGLAS CO. SURVEYORS OFFICE
T215

WC EAST 75 FT
1/4 S36 R
S1 12
TO COR W

FROM WIT. COR. T223

-1971 38" DIA HEMLOCK BT BEARS
S12 1/2°W, 20.3 FT

-1991 40" DIA. SPRUCE BT BEARS
N26°E, 46.2 FT

-1" IRON ROD BEARS S83 1/2°E, 65.2 FT

COMPASS DECL. 17 1/2°E

(CON BACK) C.S. File No 66/48-25

NEW FROM W.C.

23" DIA. HEMLOCK DOUBLE
BLAZED AND SCRIBED "WC 1/4
S1 CS BT" BEARS 558° W, 34.2 FT

15" DIA. HEMLOCK DOUBLE
BLAZED AND SCRIBED "WC 1/4
S36 CS BT" BEARS N2 1/2° W,
47.0 FT

WIT. CORNER SET 1-8-03
RANDALL W. SMITH STEPHEN J. FLAISE

SET BRASS CAP W.C. AT
HUB ESTABLISHED FOR W.C.
75 FT WEST ON SURVEY
FILE M141-40