

GOVERNMENT CORNER RESTORATION FORM

FILED

Date: 2-14-2005

Township 31S Range 02W Sec. 3

County DOUGLAS

State OREGON Date 8/26/04

No. 440600

Corner Plat: 67/10-2

Corner Designation

1/4 S3 / S10

DOUGLAS COUNTY SURVEYOR

- Condition Report Only
- Not Found
- Renewed
- Unrecorded
- Surveyed In
- Referenced Out

Previous Renewals DCSD 1961, BAUGHMAN/USFS 1978

Monument(s) Found: (Condition and Source)

FROM THE 1961 DCSD RENEWAL A 2 1/2 INCH DIAM. BRASS CAP (MARKED AS AT RIGHT) ON A 1 1/4 INCH O.D. IRON PIPE IS FIRMLY SET AND PROTRUDES APPROXIMATELY 10 INCHES ABOVE GROUND.

MONUMENT DETAIL

COUNTY SURVEYORS OFFICE

T31S R2W

1/4 S3 / S10

1961

Accessories Found:

EVIDENCE OF ONE ORIGINAL B.T.; A PINE 18 INS, NOW A FALLEN AND ROTTEN PINE SNAG APPROX. 26 INCHES DIAM. (NO BARK) WITH A PREVIOUSLY OPENED BLAZE SHOWING THE SCRIBING "1/4 S 3" BEARS N06°E, 24 1/2 FEET DISTANT (AS PER RECORD).

FROM THE 1961 DCSD RENEWAL THE ONE NEW BEARING TREE; A 9" R. FIR, NOW A 14 INCH D.B.H. DOUGLAS FIR WITH A FULLY HEALED DOUBLE BLAZE BEARS S 31°W, 14 1/2 FEET DISTANT (AS PER RECORD).

FROM THE 1978 BAUGHMAN/USFS RENEWAL THE ONE NEW BEARING TREE; A 12" D. FIR, NOW A 14 INCH D.B.H. DOUGLAS FIR WITH A FULLY HEALED DOUBLE BLAZE BEARS N68°E, 9.6 FEET DISTANT (AS PER RECORD).

