

TOWNSHIP 22 RANGE 05 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1407)

Set 1/4 sec. post, from which
 A W.Oak 30" dia., bears S.42°E., 120 lks. dist.
 A W.Oak 12" dia., bears N.80°W., 52 lks. dist.

Wilford N. Haines - Oct. 1964 - C.S. File 51/305

Found - 30" Oak S.42°E., 120 lks.
 Set 1" x 1" x 36" T-Iron.
 Scribed -13" Fir N.58 1/2°E., 56.7 ft.
 36" I.Cedar N.16°W., 84.7 ft.

Corner destroyed, burned and bulldozed per E. Bloom, Dec. 9, 1980 - M 79-64 A&B

Handwritten notes:

FD
 N-S
 1 Iron
 FD
 5 FT
 FENCE LINE
 FOUND
 RWS
 SOF 2001

Other notes:

OLD BURIED
 WIRE RUNNING
 BADLY BENT
 WITH NO POSITION
 1" BELOW SURFACE
 WEST OF BURIED
 NO BT'S

FILED

Date: 3/7/2007 By: JC

This survey consists of:

Map: _____

Narrative: _____

Corner Rpt: 67/21-13

DOUGLAS COUNTY SURVEYOR 1

C.S. File No 67/21-13