

GOVERNMENT CORNER RESTORATION FORM

FILED

Date: 3/7/2008 By: X

Township 26S Range 3W Sec. 1 County DOUGLAS This survey consists of:

State OR Date FEB. 21, 2008 No. 640700 Map: \_\_\_\_\_

Corner Designation

Narrative: \_\_\_\_\_  
Corner Rpt: 67/25-16

S 36 T. 25-3  
\*  
S 1 T. 26-3

- DOUGLAS COUNTY SURVEYOR
- Condition Report Only
  - Not Found
  - Renewed
  - Unrecorded
  - Surveyed In
  - Referenced Out

Previous Renewals 1940, 1960, 1963, 2006

MONUMENT DETAIL

Monument(s) Found: (Condition and Source)

3/4" B.C. ON 3" O.D. IRON PIPE  
PROPERLY MARKED, PROJECTS  
8" ABOVE GROUND. A 2" O.D.  
IRON PIPE IS FOUND BESIDE  
BC/IP

N/A

Accessories Found:

- 10" NOW 16" DIA. X 2 FT. TALL STUMP, PITCH POCKET VISIBLE ON TOP OF STUMP, BEARS S 47°E, 66.8 FT. (REC. S 47°E, 68.0 FT.) 1963 BT
- 36" NOW 37" DIA. HEMLOCK (NOT FIR AS REPORTED BY SCHINNELL IN 2006) BEARS N 57 1/2°E, 19.5 FT. (REC N 53°E, 17.6 FT) 1960 BT
- 12" NOW 13" FIR BEARS S 4°W, 12.5 FT. TO CENTER OF ROOT CROWN. NOTE: TREE WAS NOT SCRIBED. IS MARKED WITH UPPER BLAZE PAINTED RED, AND LOWER NOTCH W/ALUM. NAIL. DISTANCES RECORDED BY SCHINNELL ARE SLOPED AND ARE MEASURED TO TIP OF NAIL. (REC. S 4°W, 11.95 FT.) 2006 BT
- 8" NOW 9" HEMLOCK BEARS N 58°W, 14.0 FT. TO CENTER OF ROOT CROWN. NOTE: TREE WAS NOT SCRIBED. IS MARKED WITH UPPER BLAZE PAINTED RED, AND LOWER NOTCH W/ALUM. NAIL. DISTANCES RECORDED BY SCHINNELL ARE SLOPED AND ARE MEASURED TO TIP OF NAIL (REC. N 58°W, 13.68 FT.) 2006 BT

