

GOVERNMENT CORNER RESTORATION FORM

FILED

Township 33 S Range 06 W Sec. 3

County DOUGLAS Date 7-2-2008 By: JC

State OREGON Date JUNE 19, 2008

No. 40064 Map: _____

This survey consists of:

Corner Designation

Narrative: _____
Corner Rpt: 67/25-57

1/4 cor sections 3 & 4

- DOUGLAS COUNTY Only
- Not SURVEYOR
- Renewed
- Unrecorded
- Surveyed In
- Referenced Out

Previous Renewals BRIGGS 1873, BRANDT 1973, NYGREN 1994

MONUMENT DETAIL

Monument(s) Found: (Condition and Source)

DEGROOT 1996

A 1+ INCH DIAMETER SPIKE HEAD, FIRMLY SET 5 INCHES BELOW ASPHALT SURFACE OF TUNNEL RD. (FROM 1973 RENEWAL). CORNER LIES 8 FT. NORTHEASTERLY FROM CENTERLINE OF TUNNEL RD.

N/A

Accessories Found:

NO EVIDENCE OF ORIGINAL BTS FOUND.

FROM 1973 RENEWAL, ONE BT AND ONE BO FOUND. A 10" NOW A 27 INCH DBH, WHITE OAK WITH A FULLY HEALED DOUBLE BLAZE, BEARS N62°12' E, 29.8 FT. DISTANT (AS PER RECORD).

A 1 INCH DIAMETER IRON ROD, FIRMLY SET, WITH TOP APPROX. 1 INCH BE-LOW GROUND, AND AT SE EDGE OF A LARGE PONDEROSA PINE, BEARS N34° W, 34.5 FT. DISTANT (AS PER RECORD).

FROM 1994 RENEWAL, TWO THEN NEW BTS (ERRONEOUSLY IDENTIFIED AS ALDERS) NOW FOUND ASH BTS. A 26" ALDER NOW A DOUBLE TRUNK OREGON ASH, THE LARGER NE TRUNK OF WHICH IS 28 INCHES D.B.H., AND THE C.R.C. OF WHICH BEARS S59° W, 44.8 FT. DISTANT (AS PER RECORD).

AN 18" ALDER NOW AN 18" DIAM. 2 FT. TALL OREGON ASH STUMP WITH NO CLEAR BLAZE EVIDENCE, BEARS N7° W, 26.6 FT DISTANT (RECORD N3° W, 26.6')

NEW BT TAGS WITH CORRECT BEARING AND DISTANCE ARE PLACED ON BOTH OREGON ASH BTS.

C.S. File No 67/25-57

