

TOWNSHIP 30 RANGE 05 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7 & 18 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 17 Pages 7129-30)

Set a post cor. of sec. 7, 12, 13 and 18, from which

- A B.Oak 12" dia., bears N.73°E., 70 lks.
- A B.Oak 15" dia., bears S.62°E., 62 lks.
- A W.Oak 24" dia., bears S.57°W., 52 lks
- A W.Oak 30" dia., bears N.60°W., 40 lks.

Doug. County Surveyors Office - N.E. Richardson, Deputy -
Wit: Evans - May 1948 - M 20-23; C.S. File 39/171

Set 1" Gal. I.P. with brass cap mkd: Co. Surveyors Office, S7|18 T30S R5W, set 2" underground. Marked BT:
 28" Oak N.25°W., 149.5 ft. scribed S13 T30S R6W
 12" Bull Pine S.56¼°E., 68.5 ft. mkd. S18 T30S R5W.
 (Both CS BTs)

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike
- 2/9/2005 - C.S. File 67/10-6

Found - 2½" brass cap on 1¼" I.P. bent over (plumb position intact) (properly marked)
 12" now 33" Bull Pine, fully healed blaze bears S.57°E., 68.5 ft. (Rec. S.56¼°E., 68.5 ft.)
~~28" now 33" B.Oak, burned unhealed blaze bears N.26°W., 151.1 ft. (rec. dist measures to center of trunk at breast height, not center of root crown) (Rec. N.25°W., 149.5 ft.)~~

Reset - Plumb position of BC/IP was referenced. We then dug up bent BC/IP straightened & reset. BC now protrudes approx. 4" above ground.

New - 8" W.Oak double blazed & scribed "T30S R6W S13 CS BT" bears S.87¼°W., 61.7 ft.
 1¼" O.D. iron pipe at SSE corner DLC #37 bears N.17¼°W., 119.4 ft.

Note - Corner bears approx. N.70°W., 12 ft. from 3 way fence intersection. Fences running Northwesterly, Southeasterly & West.

5/16/11
REPORT AS
DOWN
WILL BE
CUT UP

DAVID STEWART
541-817-4620

Per phone call

FILED
 Date: 5/31/2011 By: JC
 This survey consists of:
 Map: _____
 Narrative: _____
 Corner Rpt: CS 67/33-37

DOUGLAS COUNTY
SURVEYOR

C.S. File No 67/33-37