

(1)  
FILED

MAY 2 2017

SEPT 22, 2016

T30S, R04W, PLSS 400500

SECTION CORNER  $\frac{S9}{S16} | \frac{S10}{S15}$   
FALLS IN RIVER

THEREFORE A WITNESS CORNER  
IS SET ON THE SECTION LINE  
BETWEEN SECTIONS 10 AND ~~15~~  
165 FEET EASTERLY.

THE WITNESS CORNER IS MON-  
UMENTED WITH A 2 1/2 INCH  
DIAM. BRASS CAP MARKED  
" COUNTY SURVEYORS OFFICE"  
T30S R4W

165' W  $\frac{S9}{S16} | \frac{S10}{S15}$  WC

2016

ON A 1 1/2 INCH I.D. X 32 INCH

C.S. File No 67/44-1

(OVER)

DIETZGEN NO. 385-5

(2)

LONG IRON PIPE, SET PLUMB  
WITH BRASS CAP FLUSH WITH  
GROUND.

BEARING TREES EST' B. FOR B. C.

A 21 INCH DIAM. ENGLISH WALNUT  
SCRIBED "BT" ON A LOW SINGLE  
BLAZE; BEARS  $N 16^{\circ} E$ ,  $173 \frac{1}{2}$  FT.  
DISTANT. AN 8 INCH SPIKE NAIL  
SET IN THE TOP OF THE GRAFTING  
BASE AT THE SE SIDE CENTER  
OF THIS B.T. BEARS  $N 16^{\circ} 21' 15" E$ ,  
 $173 \frac{1}{3}$  FT. DISTANT

A 34 INCH DIAM. BLACK OAK  
(FIRST SCRIBED AS A 16 INCH B. OAK  
FOR WITNESS CORNER SET IN 1963)

CONT'D

(3)

T 305 R 4 W PLS 5 400500 CONT'D

WITH A FULLY HEALED SINGLE

BLZ.; BEARS N 53° W, 276 FT.

DISTANT. AN 8 INCH SPIKE NAIL

SET IN THE NE SIDE CENTER AT

THE BASE OF THIS B.T. BEARS

N 50° 19' 34" W, 276<sup>3</sup> FT. DISTANT

DIETZGEN NO. 385-5

FILED

MAY 2 2017

FEB. 21, 2017

T30S, R04W, PLSS

SOUTH WITNESS COR. S9 | S10

S16 | S15

FROM 1922 DC50 SURVEY FILED AS

M2-9:

A STONE 3 INS. X 6 INS. X 14 INS. LONG

BURIED 1 FT. BELOW GROUND AND

TIPPED SOUTHERLY.

THE TOP OF THIS STONE SHOWS

CHISEL MARKS, POSSIBLY A

CROWFOOT, AS DESCRIBED IN

1959 SURVEY FILED AS RM 1-28.

MEASURING FROM THE BASE

OF THE STONE IF IT WAS SET PLUMB

WE FIND THE 6" W. OAK NOW A

16' INCH DIAM. WHITE OAK, BLAZE NO

LONGER EVIDENT; BEARING S39°E, 43 ± FT.  
DISTANT (AS PER RECORD).

DIETZGEN NO. 385-5

87/44-1

C.S. File No

SOUTH W.C. TO S9/S10 CONT'D  
S16/S15

\*  
(TO BE REVISED WITH NEW DCSD  
MAP REFERENCE)

AT POSITION DETERMINED BY

SURVEY (?) WHICH CONFIRMS POS-

ITION OF FOUND STONE AND W. OAK B.T.

SET A 2 1/2 INCH DIA. BRASS CAP

MARKED "DOUGLAS COUNTY SURVEYOR"

T 30S R 4W

WC S9/S10  
S16/S15

NORTH

245.8'

2017

ON A 1 INCH I.D. X 32 INCH IRON PIPE

SET PLUMB PROTRUDING 2 INS. ABOVE

GROUND. FOUND STONE MONUMENT

IS SET ON SOUTH EDGE OF B.C.

MONUMENT WITH TOP FLUSH WITH  
GROUND.

(OVER)

NEW B.T.S MEASURED FROM  
BRASS CAP

A 7 INCH DIAM. W. OAK SCRIBED  
"SWC CS" "BT" ON A DOUBLE  
BLAZE; BEARS  $N 19^{\circ} 14' E$ , 14<sup>2</sup> FT.  
DISTANT.

A 1 1/2 INCH DIAM. MADRONE SCRIBED  
"SWC" "CSBT" ON A DOUBLE  
BLAZE; BEARS  $S 06^{\circ} 12' W$ , 75<sup>2</sup> FT.  
DISTANT.

OTHER REFERENCE:

THE EAST WITNESS CORNER

TO S 9 | S 10 A DCSD BRASS CAP  
S 16 | S 15

MONUMENT BEARS  $N 34^{\circ} 55' 04'' E$ ,  
296 ~~58~~ FT. DISTANT.

AND RAY BROWN  $5/8$ " IR/PLST CAP  
 $N 03^{\circ} 30' W$ , 10<sup>2</sup> 5 FT