

OCT 3

TOWNSHIP 29 RANGE 03 POINT IDENTIFIER # 536700

PRIMARY CORNER DESCRIPTION C C for Secs 34 & 35 only, T28-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by William N. Gibb, Deputy Surveyor, under Contract #783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5557)

-----²⁴⁴²⁰-----

Intersect S. bdy., 370 lks. S.89°18'W. of N. 1/4 Cor. Sec. 2, T29-3. Set Fir stake 3 ft. long, 4" sq., 24" in the ground for closing cor. secs. 34 and 35, marked C C T28S R3W on N.; S35 on E.; and S34 on W. face, with 2 grooves on E. and 4 grooves on W. face, from which

A Fir 6" dia., bears N.52°E., 20 lks. dist. mkd. T28S R3W S35 BT. ¹³²⁰

A Laurel 6" dia., bears N.48°W., 28 lks. dist. mkd. T28S R3W S34 BT. ¹⁸⁴⁸

Douglas Co. Surveyors Office - James Byron, Deputy, Milo Godfrey; Clete Putnam, crew - Feb. 2, 1960 - C.S. File 49/47

✓ Found - Orig. 6" now 20" Laurel N.48°W., 18.5 ft., shows good "28S R3W 34 CC" scribing.
No trace of orig. NE. BT found.

Set Brass cap at cor. mkd: County Surveyors Office
T 28 S R 3 W
S34 S 35
T 29 S
1960

✓ New BTs- 5" R.Fir bears N.16½°E., 24.3 ft. scribed S35 CSBT
15" R.Fir bears N.51°W., 22.5 ft. scribed T28S R3W CC
S34 CS BT.

Fd. OK by D. Edwards, Oct. 1999 - M133-43

FOUND IN GOOD CONDITION Oct. 3, 2018
Stephen Fleuse & Jeff Larsung
Douglas Co. Surveyors Office

FILED
Date: 10-11-2018 By: X
This survey consists of:
Map: _____
Narrative: _____
Corner Rpt: CS 67/45-8
DOUGLAS COUNTY SURVEYOR

C.S. FILE 67/45-8 ¹