

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3318-19)

-----  
Set a post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 13, 14, 23 and 24 marked T24S S13 on NE.; R8W S24 on SE.; S23 on SW.; and S14 on NW. faces, with 3 notches on S. and 1 notch on E. edges, from which

30" x 24" FT

~~PUTTED~~ ~~ETMP~~ A Fir 15" dia., bears N.55°E., 79 lks. dist. mkd. T24S R8W S13 BT. <sup>52'4"</sup>  
~~TIPPERCUT~~ ~~RATTED STAMP~~ A Fir 18" dia., bears S.36°E., 25 lks. dist. mkd. T24S R8W S24 BT. <sup>16 50</sup>  
~~FILE~~ ~~OPEN~~ A Fir 24" dia., bears S.18°W., 85 lks. dist. mkd. T24S R8W S23 BT. <sup>56 10 53 4 HORIZ.</sup>  
A Fir 48" dia., bears N.77°W., 78 lks. dist. mkd. T24S R8W STUMPS14 BT. <sup>51 48</sup>

F7/SB

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; C. Putnam, crew - Nov. 1960 - C.S. File 49/41

-----  
Found all orig. BTs. All check for bearing and distance and size and all show scars. Orig. NW. BT now stump only. Orig. SW. BT, now down. SEE ABOVE

Set Brass cap at cor. mkd: County Surveyors Office  
T 24 S R 8 W  
S 14 | S 13  
S 23 | S 24  
1960

New BTs- 8" R.Fir bears S.74°W., 17.7 ft. scribed S23 T24S R8W CS BT.  
9" W.Fir bears N.42°W., 53.8 ft. scribed S14 T24S R8W CS BT.  
15" R.Fir bears S.2°E., 39.0 ft. scribed S24 T24S R8W CS BT.  
15" R.Fir bears N.33°E., 42.0 ft. scribed S13 T24S R8W CS BT.

Found OK by R. Rice, June 2003 - M142-47

DCSO SJF & JL

FD OK

3/19/2019

FILED  
Date: 3/28/2019 By: [Signature]  
This survey consists of:  
Map: \_\_\_\_\_  
Narrative: \_\_\_\_\_  
Comer Rpt: CS67/46-3

DOUGLAS COUNTY SURVEYOR

C.S. FILE 67/46-3