

TOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 039040

PRIMARY CORNER DESCRIPTION Most W. NW. cor. Scholfield DLC 39

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO DLC survey by Socrates Scholfield, Deputy Surveyor, under Contract dated March 31, 1859

Set stake, from which
 A Spruce 12" dia., bears South, 36 lks.
 A Spruce 30" dia., bears S.89°W., 45 lks.
 A Fir 30" dia., bears N.49°E., 10 lks.

FILED
 Date: 8/7/2019 By: X
 This survey consists of:
 Map: _____
 Narrative: _____
 Corner Rpt: CS 67/46-4

BLM resurvey by Glenn F. Goodson, Scott R. McIntyre and **DOUGLAS COUNTY SURVEYOR** R. McMullin, Cadastral Surveyors - Under Group #106 (Surveyed June/Sept. 1981 - (DCSO records Vol. 44 Page(s) 17123)

Point for the NW. cor. of DLC #39, determined by the Grant Boundary Method; there is no remaining evidence of the original corner.
 Set an alum. post, 28" long, 2½" dia., 24" in the ground, with alum. cap mkd:

S 18 / DLC 39

1981

from which
 A Fir 15" dia., bears N.74°E., 46½ lks. dist. mkd. DLC 39 BT.
 A Fir 27" dia., bears N.75°W., 9 lks. dist. mkd. DLC 39 BT.

Fd. OK, Jan/March 1982 by Clayton Martin - M 91-61

NEW TAGS
+ FOUND CARSONITE
POST'S

NO GPS DUE TO
RECEPTION.
UCSO - SJF & JL
6/19/2019

U.S. DEPARTMENT OF THE INTERIOR

6/19/19

S18 / DLC 39

1981
BUREAU OF LAND MANAGEMENT

FIR 15" N74°E, 30⁶⁹

FIR 27" N75°W, 5⁹⁴

CARSONITE POSTS

≈ N 35°E 44

SOUTH 44

C.S. FILE 67/46-4