

FND OK 7/7/20

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 600300

DCSO  
Stephen Flaysr

PRIMARY CORNER DESCRIPTION Sec. Cor. for 23, 24, 25 and 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Jeff  
Lorsung

Original, Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO Records, Volume 9 Page 3670)

Set a cedar post, 4 ft. long, 4" sq., 24" in the ground for cor., mkd. T25S S24 on NE., R3W S25 on SE., S26 on SW., and S23 on NW. faces, with 2 notches on S. and 1 notch on the E. edges, from which

- A Hemlock 36 dia., bears N.15°E., 34 lks. dist., mkd. T25S R3W S24 BT.
- A Hemlock 18" dia., bears N.30°W., 65 lks. dist., mkd. T25S R3W S23 BT.
- A Fir 24" dia., bears S.40°E., 80 lks. dist., mkd. T25S R3W S25 BT.
- A Yew 12" dia., bears S.65°W., 10 lks. dist., mkd. T25S R3W S26 BT.

FILED  
 Date: 7-13-2020 By: XC  
 This survey consists of:  
 Map: \_\_\_\_\_  
 Narrative: \_\_\_\_\_  
 Corner Rpt: CS 67/46-35

**DOUGLAS COUNTY SURVEYOR**

GLO Dependent Resurvey by Norman D. Price, Under Special Instructions dated April, 5, 1940. (DCSO records, Volume 27 Pages 11542-43)

The original cor. of secs. 23, 24, decayed point of a squared wooden s remain. At point for corner, set a 2" dia., 28" in the ground, with d stake deposited at the base, for co. 26, with brass cap mkd.

LAT: 43.369051642  
LONG: -123.012617466

- |  |        |
|--|--------|
|  | T25S R |
|  | S23    |
|  | S26    |
|  | 194    |
- A Fir 36" dia., bears N.11½°E. blaze healed. (Old BT)
  - A Fir 38" dia., bears S.42°E., blaze healed. (Old BT)
  - A yew 12" dia., bears S.45°W. scribe marks on badly weat (Old BT)
  - A Hemlock, 30" dia., bears N.2! partial scribe marks visib old blaze. (Old BT)
  - A Fir 36" dia., bears S.51¼°W., 72 lks. dist., mkd. T25S R3W S26 BT. (New BT)

Doug. County Surveyors Office - V.R. Tracy and crew. Sept. 1, 1966 - C.S. File 54/27-65

Found - GLO brass cap mkd. in 1943.  
continued next page

1  
C.S. FILE 67/46-35

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 23, 24, 25 and 26

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

Orig. 12" now 13" Yew S.45°W., 6.6 ft. fragmentary scribe marks on rotted face. Rescribe "T25S R3W S26 CS BT".

Orig. 30" now 32" Hemlock N.25°W., 40.9 ft. partial scribe marks visible on nearly healed blaze.

All other BTs destroyed by recent logging.

New BTs - 9" Hemlock N.9°W., 52.4 ft. mkd. T25S R3W S23 CS BT.  
11" Hemlock N.40°E., 40.0 ft. mkd. T25S R3W S24 CS BT.  
9" Hemlock S.18°E., 148.0 ft. mkd. T25S R3W S25 CS BT.

Found OK, Nick Juliano, Dec. 1976, C.S. 58/130  
Fd. Ok by D. Edwards, added 6 ft steel post 2' North - 12/2006 - M151-74

BLM Dependent resurvey by A. Bert Skeesick & Kenneth W. Saveland, Cadastral Surveyors and Robert H. Browning, Survey Tech, under Group No. 2212 surveyed July/Oct. 2008 - (DCSO records Vol. 57 Page(s) 22420-1)

-----

The cor. of secs. 23, 24, 25, and 26, perpetuated by the Douglas County Surveyor's Office in 1966, monumented with an iron post, 2" dia., firmly set, projecting 9" above ground, with brass cap (properly) mkd. from which the remains of the original bearing trees

A roothole bears N.11½°E., 22.4 ft., alongside of which is an uprooted, sawed, decayed hemlock stump, 40" dia., with no marks visible.

A roothole bears S.42°E., 52.8 ft., alongside of which is a down, decayed fir snag, 34" dia., with a healed blaze.

A yew, 13" dia., bears S.45°W., 6.6 ft., with scribe marks BT visible on a partially healed blaze.

and the remains of a bearing trees mkd. by Price

A sawed fir stump, 37" dia., bears S.51¼°W., 47.5 ft., with a healed blaze.

and the remains of bearing trees mkd. by the Douglas County Surveyor's Office

A hemlock, 23" dia., bears N.41½°E., 40.3 ft., with a healed blaze.

A roothole bears S.18¼°E., 148.3 ft., alongside of which is a down, decayed hemlock snag, size indeterminate, with no marks visible.

continued next page

2

CS 67/46-35

TOWNSHIP 25 RANGE 03 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Cor. Secs. 23, 24, 25, & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A hemlock, 19" dia., bears N.9¾°W., 52.4 ft., with fragmentary scribe marks visible on a partially healed blaze.  
and new bearing trees  
A fir, 13" dia., bears S.63¾°E., 22.3 ft., mkd. T25S R3W S25 BT.  
A fir, 13" dia., bears S.13¾°W., 16.6 ft., mkd. T25S R3W S26 BT.  
Corner is located on a gradual E. slope.

CS 67/46-35