

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 30

LAT: 43.635115069

otion _____
otion _____
otion _____
otion _____

2/4/20
FNP

LONG: -123.457928309

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664 dated May 23, 1896 (DCSO records Vol. 4 Page(s) 1487)

Set a Dogwood post, 3 ft. long, 4" sq., 24" in the ground, for 1/4 sec. cor. mkd. 1/4 S on N. face, from which

A Fir 24" dia., bears N.87°E., 157 lks. dist. mkd. 1/4 S BT

A Fir 30" dia., bears S.5°E., 128 lks. dist. mkd. 1/4 S BT

This cor. is on the westerly slope of spur, about 400 ft. above creek.

103 62
84 48

Wilford N. Haines - For: E.G. Whipple Mill - 1955 - Map made Jan. 1956 - M 2-13

This corner set by proportional measurement between the NE and NW corners of sec. 30.

Set angle iron with brass cap inscribed, "Survey Point-Wilford N. Haines 239"

Scribed two new BTs:

44" D.Fir S.27°E., 99.6 ft.

40" I.Cedar N.14°W., 132.3 ft.

FILED
Date: 12/2/2020 By: X
This survey consists of:

Map: _____
Narrative: _____
Corner Rpt: CS 67/46-37

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor Under Group No. 2653, Surveyed June/July 2012 - DCSO records Vol. 58 Page(s) 22991

DOUGLAS COUNTY
SURVEYOR

Point for the 1/4 sec. cor. of secs. 19 & 30, at proportionate There is no remaining evidence of the original corner.

Set a stainless steel post, 28" long, 2 1/2" dia., 26" in the ground, with brass cap mkd.

1/4 $\frac{S\ 19}{S\ 30}$
2012

from which

A fir, 12" dia., bears S.78 3/4°W., 23.2 ft., mkd. 1/4 S30 BT.

A fir, 19" dia., bears N.7 3/4°W., 60.8 ft., mkd. 1/4 S19 BT.

Bury a magnet in a white plastic case at the base of the stainless steel post.

Corner is located on a SW. slope, 95 ft. W. of a graveled road, 10 ft. wide, bears S.50°E. and N.68°W., and 25 ft. S. of the same road, 10 ft. wide, bears S.82°E. and West.

From this cor., a point established as the 1/4 sec. cor. of secs. 19 and 30 by Haines, in 1955, bears S.81°49'29"W., 25.41 ft., monumented with a "T" shaped iron rod, 3/4" dia., firmly set, projecting 13" above ground, with brass disk on top, mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE, from which bearing trees mkd. by Haines continued next page

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor for Secs 19 and 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 54" dia., bears S.26¼°E., 99.3 ft., with a healed blaze.
A cedar, 61" dia., bears N.13¼°W., 132.0 ft., with a healed blaze.
This point was not correctly positioned and is not utilized in the course of this survey.