

TOWNSHIP 29 RANGE 02 POINT IDENTIFIER # 500200

FND OK  
9/24/20

PRIMARY CORNER DESCRIPTION Sec. Cor. for 26, 27, 34 and 35

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6252-53)

Set an iron post 3 ft. long, 2" dia., 24" in the ground for cor. of secs. 26, 27, 34 and 35, with brass cap marked:

|           |
|-----------|
| T29S R2W  |
| S27   S26 |
| S34   S35 |
| 1917      |

from which

- A Fir 10" dia., bears N.63°E., 78 lks. dist. mkd. T29S R2W S26 BT.
- A Fir 24" dia., bears S.34°E., 46 lks. dist. mkd. T29S R2W S35 BT.
- A Fir 24" dia., bears S.17°W., 61 lks. dist. mkd. T29S R2W S34 BT.
- A Cedar 10" dia., bears N.29°W., 98 lks. dist. mkd. T29S R2W S27 BT.

Douglas Co. Surveyors Office - Clell Goodwin; Vic Cangie, crew - Sept. 22, 1975 - C.S. File 57/36-11

Found - 1917 GLO brass cap, properly stamped, projecting 8" out of the ground and apparently undisturbed.

An Orig. 24" now 38" Fir bears S.34°E., 30.4 ft.

Orig. 10" now 16" Cedar bears N.29°W., 65.4 ft. (call N.29°W., 64.7 ft.)

Orig. 24" Fir now a rotted stump, bears S.17°W., 40.8 ft. (Call S.17°W., 40.3 ft.)

No sign of orig. NE. BT, which has been removed by road construction.

New BTs- 13" Fir scribed "T29S R2W S34 CS BT" in a double blaze, bears S.15½°W., 27.5 ft.

12" Cedar scribed "T29S R2W S26 CS BT" in a double blaze, bears N.72½°E., 21.1 ft.

Mark Smalley, for Scott Timber Co. Nov. 1997 - M 124-68

Found - 1917 GLO brass cap on iron pipe.

22" Cedar, N.73°E., 21.9 ft. healed, no record

14" Cedar, N.32°E., 23.8 ft. snag, no record

24" Fir, S.34°E., 30.4 ft. stump

24" Fir, S.17°W., 40.3 ft. healed

34" Cedar, N.29°W., 64.7 ft. healed

New Accessories -

12" Cedar, N.86°W., 14.6 ft. scribed "S27 BT"

12" Fir, N.18°E., 13.8 ft. scribed "S26 BT"

FILED

Date: 12/2/2020 By: X

This survey consists of:

Map: \_\_\_\_\_

Narrative: \_\_\_\_\_

Corner Rpt: CS 67/46-41

DOUGLAS COUNTY SURVEYOR

LAT: 43.019288031

LONG: -122.922263691

C.S. FILE 67/46-41