

FND OK

LAT: 43.707494733, LONG: -123.604220884

10/12/20

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Cor Secs 25, 26, 35, & 36

SEE PG 2 FOR CHANGES

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 838)

Set post 6" dia., 4 ft. long with marked stone 12" in ground for corner to secs. 25, 26, 35 & 36, marked T21S, S 25 on NE, R8W, S 36 on SE, S 35 on SW, S 26 on NW face with one notch on E & S edge from which:

- Fir, 18" dia. bears N.76°W., 36 lks., mkd: T21S R8W S26 BT
- Fir, 12" dia. bears S.14°W., 33 lks., mkd: T21S R8W S35 BT
- Fir, 6" dia., bears S.70°E., 40 lks., mkd: T21S R8W S36 BT
- Fir, 18" dia. bears N.70°E., 61 lks., mkd: T21S R8W S25 BT

BLM dependent resurvey by Marvin J. Lytle, Palmer Norseth, Thomas A. Tillman, Raymond M. Bicknell, Joseph S. Gawron, and Hans W. Thielsen, Cadastral Engineers, under Group #304, Surveyed Aug. 1952 thru Oct. 1954 - (DCSO recs. Vol. 30 Page(s) 12557)

The cor. of secs. 25, 26, 35 & 36, determined at the record bearing & dist. from each of the remaining orig. BTs, as follows:

- A Fir snag, 22" dia., bears N.70°E., 61 lks., showing a burned resinous blaze facing SW.
- A Fir stump, 12" dia., bears S.72½°E., 40 lks., with old scribe marks still visible. (Rec. bearing S.70°E.)
- A stump hole, bears S.14°W., 33 lks.
- A Fir, 37" dia., bears N.77½°W., 36 lks., showing old axe marks on scarred SE face. ( Rec. bearing, N.76°W.)

At the corner point Set an iron post, 3 ft. long, 1" dia., 274" in the ground, with brass cap marked:

|      |      |
|------|------|
| T21S | R8W  |
| S 26 | S 25 |
| S 35 | S 36 |
| 1952 |      |

- from which
- A Fir, 28" dia., bears N.74°E., 124 lks., mkd: T21S R8W S25 BT.
  - A Fir, 23" dia., bears S.18°E., 76 lks., mkd: T21S R8W S36 BT.
  - A Fir, 45" dia., bears S.26½°W., 42 lks., mkd: T21S R8W S35 BT.
  - A Fir, 20" dia. FILED bears N.73½°W., 94 lks., mkd: T21S R8W S26 BT.

Date: 12/2/20 By: [Signature]

This survey consists of:

continued on Map page \_\_\_\_\_

Narrative: \_\_\_\_\_  
Corner Rpt: CS 67/46-45

DOUGLAS COUNTY SURVEYOR

C.S. FILE 67/46-45

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Cor. Secs 25, 26, 35, & 36

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2115, surveyed January/May 2007 (DCSO records Vol. 56 Page(s) 22055-6)

The cor. of secs. 25, 26, 35, and 36, monumented with an iron post, 2" dia., firmly set, projecting 9" above ground, with brass cap (properly) mkd.

from which the remains of an original bearing tree

A decayed fir stump, 36" dia., bears N.77½°W., 23.8 ft., no marks visible.

and the remains of the BTs mkd. by Lytle, et al., in 1952-54

A decayed fir stump, 30" dia., bears N.7¼°E., 81.8 ft., no marks visible.

A decayed fir stump, 23" dia., bears S.18°E., 50.2 ft., no marks visible.

A decayed fir stump, 42" dia., bears S.26½°W., 27.7 ft., no marks visible.

A decayed fir stump, size indeterminate, bears N.73½°W., 62.0 ft., no marks visible.

and bearing trees mkd. by person(s) unknown

— A fir, 12" dia., bears S.28°E., 20.9 ft., with a healed blaze with a nail and washer in face, and a nail on the right side center.

— A fir, 14" dia., bears S.37¼°W., 16.7 ft., with a healed blaze with a nail and washer in face, and a nail on the right side center.

— A fir, 15" dia., bears S.86½°W., 17.2 ft., with a healed blaze with a nail and washer in face, and a nail on the right side center.

and new bearing trees

— A fir, 10" dia., bears N.24½°E., 53.3 ft., mkd. T21S R8W S25 BT.

— A fir, 19" dia. bears N.6°W., 85.3 ft mkd. T21S R8W S26 BT  
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

A steel fence post is alongside the cor. and a fir, 2 ft. dia., bears N.20°W., 20 ft., with a BLM location tag.

AS  
DESCRIBED

12" x 10" SAWN  
20" x 7" FT  
SAWN STUMP