

4/23/20

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 500700 FND OK

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2 & 3; 34 & 35, T20-8 GPS

Alias \_\_\_\_\_ Description LAT: 43.776871266 LONG: -123.621287369

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

FILED

Date: 12/28/2020 By: \_\_\_\_\_

This survey consists of \_\_\_\_\_

Map: \_\_\_\_\_

Narrative: \_\_\_\_\_

Corner Rpt: CS 67/46-51

**DOUGLAS COUNTY SURVEYOR**

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. Page(s) 453-54)

-----

Set post 6" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 2, 3, 34 and 35, marked T20S S35 on NE.; R8W S2 on SE.; T21S S3 on SW.; S34 on NW. faces with 4 notches on W. & 2 on East edges; from which

- Fir 30" dia., bears N.82°W., 25 lks. dist. mkd. T20S R8W S34 BT.
- Fir 40" dia., bears S.41°W., 40 lks. dist. mkd. T21S R8W S3 BT.
- Fir 40" dia., bears S.35°E., 27 lks. dist. mkd. T21S R8W S2 BT.
- Fir 6" dia., bears N.92°E., 47 lks. dist. mkd. T20S R8W S35 BT.

BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #292, Surveyed June/Oct. 1950 - (DCSO records Vol. 27 Page(s) 11327-28)

The Sec. Cor., determined at the record bearing and distance from the original SE. bearing tree as follows:

- A Fir 50" dia., bears S.35°E., 27 lks. dist. mkd. with a scribe on the bark T21S R8W S2.
- A Fir 40" dia., bears S.44°W., 26 lks. dist., blazed on the bark, but no scribe marks remain. (Rec. brg. S.41°W., 40 lks. dist.)
- A Fir 50" dia., bears N.88°W., 47 lks. dist., with partial scribe marks visible on the bark.

The record calls for:

- A Fir 6" dia., bears N.92°E., 47 lks. dist.
- A Fir 30" dia., bears N.82°W., 25 lks. dist.

Wright evidently confused these trees when completing the returns.

At the corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T 20 S R 8 W
S 34   S 35
S 3   S 2
T 21 S
1950

from which new bearing trees:

- A Hemlock 10" dia., bears N.30°E., 39 lks. dist. mkd. T20S R8W S35 BT.
- A Fir 50" dia., bears S.59¼°W., 59 lks. dist. mkd. T21S R8W S3 BT.

1  
CS 67/46-51