

Filed 11/23/2021

FNA OK

MMGPS 7/22/21

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9 SEE PG 2 FOR REF. CHNGS

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2595)

-----  
Set stone 16 x 12 x 8 ins., 10" in the ground for cor. to secs. 4, 5, 8 and 9, marked with 5 notches on S. and 4 notches on E. edges, from which

- A Fir 30" dia., bears N.15°E., 57 lks. dist. mkd. T23S R8W S4 BT.
- A Fir 20" dia., bears S.10°E., 70 lks. dist. mkd. T23S R8W S9 BT.
- A Fir 30" dia., bears S.21°W., 30 lks. dist. mkd. T23S R8W S8 BT.
- A Fir 24" dia., bears N.67°W., 38 lks. dist. mkd. T23S R8W S5 BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Jan. 1966 - C.S. File 54/12-40

-----  
Found - Orig. 24" now 40" Fir, N.67°W., 25.1 ft. Open and find "S5" scribe.

All other orig BTs now only badly decayed remains of stumps, apparently destroyed by old fire.

Set Brass cap at cor. mkd: County Surveyors Office  
(Set in mound of stone)

T 23	S R 8 W
S 5	S 4
S 8	S 9
1966	

- New BTs- 13" D.Fir S.21°W., 23.0 ft. mkd. T23S R8W S8 CSBT
- 12" D.Fir S.18°E., 15.4 ft. mkd. T23S R8W S9 CSBT
- 8" D.Fir N.64°E., 5.7 ft. mkd. T23S R8W S4 CS BT.
- 5" D.Fir N.28°W., 8.8 ft. mkd. S5 CS BT.

Corner lies 6 ft. East of top of ridge, sloping North.

-----  
Corner referenced out by DCSO for road construction, L. Monrean, Deputy - Sept. 4, 1979 - C.S. File 59/30

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - Teresa Buley, wit. - Nov. 30, 1981 - C.S. File 61/29-37

-----  
(Referenced out notes now attached to the field notes in C.S. File 61/29)

Found - 5/8" Iron rod with alum. cap stamped "BO 2" along with PK nail in a 24" Fir for a backsight in 1979.

5/8" I.Rod with alum. cap stamped "BO 1" per 1979. PK nail used for backsight in 20" Fir, is gone.

(Cont. Next Page)

CS 67/51-13

TOWNSHIP 23 RANGE 08 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Sec Cor. for 4, 5, 8 and 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Brass cap per 1966 was removed per the reference notes of 1979.

The above mentioned reference monuments were used to reestablish corner position, from which

42" Fir with partially opened scar, bears N.67°W., 25.1 ft.

14" Fir with good scar, bears S.18°E., 15.4 ft.

10" Fir with good scar, bears N.64°E., 5.7 ft.

All other BTs mentioned in reference notes were taken out by road construction.

Using reference monument "BO 2", along with its backsight, I establish a position at record distance (per ref. notes of 229.48 ft.) Since "BO 1" no longer has a backsight, I can't check line from it, but do confirm rec. distance (per ref. notes of 62.4 ft.)

At this point, I SET a 1" x 30" I.P. with brass cap attached, stamped: "Douglas Co. Surveyor T23S S5 S4 S8 S9 R8W 1981". Since I hit bedrock down about 12", I build a large mound of dirt and stones approx. 18" high around the brass cap, which is no East shoulder of new road.

New BT - 10" Fir scribed "T23S R8W S8 CS BT" in double blaze bears S.34°W., 62.0 ft.

Fd. OK, Dec. 1995 by C. Mulkins - M 123-32

Ronald L. Rice, Ward NW - Aug. 8, 2008 - C.S. File 65/63-26

Found - 3" brass cap (properly mkd) dated 1981 with the following accessories:

44" D.Fir bears N.67°W., 25.1' - healed face

24" D.Fir bears S.13°E., 15.4' - healed face

15" D.Fir bears S.34°W., 62.0' - healed face

Record 15" D.Fir bearing N.64°E., 5.7' - down, out of position.

New BT - 19" D.Fir bears N.38°E., 26.9' - blazed, scribed "T23S R8W S4 BT"

Note - Corner has steel post adjacent to it. All BTs have red painted bands & yellow tags. Compass decl. 17°E.

Found & used by BLM resurvey by Michael O. Jones, Cadastral Surveyor under special instructions dated May 27, 2009 - Surveyed June/July 2009 - (DCSO records BLM plat 2011 & Vol. 56 Page 22267)

Latitude 43°35'29.48"N. Longitude 123°39'49.68"W.  
(NAD 1983 (CORS 96))

Fd per rec. 8/2019 - C.S. File 65/102-73 by R. Quimby

CS 67/51-13